

63365-1 ✓ ACTIVE

FASTON | FASTON 250


TE Internal #: 63365-1

Quick Disconnects, Receptacle, 14 – 10 AWG Wire Size, 2.08 – 5.26 mm² Wire Size, Mating Tab Width 6.35 mm [.25 in], Straight, Brass, FASTON 250

[View on TE.com >](#)



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **2.08 – 5.26 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Connection Capacity	Single
---------------------	--------

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Contact Features

Quick Disconnect Terminal Type	Receptacle
--------------------------------	------------

Mating Tab Width	6.35 mm [.25 in]
------------------	------------------

Mating Tab Thickness	.81 mm [.032 in]
----------------------	------------------

Terminal Orientation	Straight
----------------------	----------

Contact Base Material	Brass
-----------------------	-------

Terminal Plating Material	Unplated
---------------------------	----------

Crimp Type	F-Crimp
------------	---------

Barrel Type	Open
-------------	------

Termination Features



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Mating Retention Type	Dimple
-----------------------	--------

Dimensions

Terminal Material Thickness	.46 mm[.018 in]
-----------------------------	-----------------

Product Length	19.69 mm[.775 in]
----------------	-------------------

Compatible Insulation Diameter Range	3.81 – 5.08 mm[.15 – .2 in]
--------------------------------------	-----------------------------

Wire Size	2.08 – 5.26 mm ²
-----------	-----------------------------

Usage Conditions

Insulation Option	Uninsulated
-------------------	-------------

Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]
-----------------------------	----------------------------

Industry Standards

Agency/Standard	CSA, UL
-----------------	---------

Packaging Features

Packaging Quantity	9000
--------------------	------

Packaging Method	Strip/Reel
------------------	------------

Other

Line	Budget
------	--------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------

EU ELV Directive 2000/53/EC	Compliant
-----------------------------	-----------

China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
---	---

EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
--	---













Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
-----------------	---

Solder Process Capability	Not applicable for solder process capability
---------------------------	--

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts

 <p>TE Part # 314917-1 EXT TL 250 U-POD STR IS9726</p>	 <p>TE Part # 58525-1 PROCRIMPER TOOL & DIE</p>	 <p>TE Part # 7-2150237-7 OCEAN_2.0_SPARE_PART_KIT-130F2100</p>	 <p>TE Part # 735211-2 250 FASTON REC 14-10 AWG TPBR</p>
 <p>TE Part # 2150237-1 OCEAN_2.0_APPLICATOR-E-130F2100</p>	 <p>TE Part # 2150237-2 OCEAN_2.0_APPLICATOR-E-130F2100</p>	 <p>TE Part # 314916-1 INSER TL 250 U-POD STR IS9725</p>	 <p>TE Part # 58525-2 PROCRIMPER DIE</p>
 <p>TE Part # 7-2150237-1 OCEAN_2.0_APPLICATOR-E-130F2100</p>	 <p>TE Part # 2-2150237-1 OCEAN_2.0_APPLICATOR-E-130F2100</p>	 <p>TE Part # 2-2150237-2 OCEAN_2.0_APPLICATOR-E-130F2100</p>	 <p>TE Part # 90120 DAHT 250 FASTON REC 14-10 ASSY</p>

Also in the Series | **FASTON 250**



Compression Connectors(4)



Crimp Terminal Housings(142)



Insertion & Extraction Tools(6)



Magnet Wire Terminals(1)



PCB Terminals(135)





Quick Disconnects(445)



Splices(4)

Customers Also Bought

TE Part #2213480-1
Z50 Low Profile LED HoldersTE Part #5-1630186-2
HSA50 1R8 1%TE Part #322906
TERMINAL,SOLIS R 90DEG 1/0 3/8TE Part #1-480318-9
02P CMNL PLUG HSG F/H BLKTE Part #40524
RING TERMINAL 12-10 AWG TPBRTE Part #1-1423673-2
W51-A122B1-10=CKTBKR,THERM,ROCTE Part #1744036-3
03P ECONOMY POWER .200 CL HSGTE Part #A13402-000
BOW-OCP2-24S-NFF

Documents

Product Drawings

[250 FASTON REC 14-10 AWG BR](#)

English

CAD Files

Customer View Model

[ENG_CVM_CVM_63365-1_AF.2d_dxf.zip](#)

English

[3D PDF](#)



3D

Customer View Model

[ENG_CVM_CVM_63365-1_AF.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_63365-1_AF.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[82004 FASTON Terminals \(Insulated and Uninsulated\) Catalog - FASTON Receptacles Section](#)

English

Product Specifications

[Application Specification](#)

English

Product Environmental Compliance

[TE Material Declaration](#)

English

Agency Approvals

[CSA Certificate](#)

English

[CSA Certificate](#)

English