TE Internal #: 6337194-1

DC Jack Connectors, Board-to-Board, 2 Position, .087 in [2.2 mm] Centerline, Plug, 100 VDC, Vertical, Printed Circuit Board, Power &


Signal

View on TE.com >



Connectors > PCB Connectors > Battery Connectors & Holders > DC Jack Connectors











Connector System: Board-to-Board

Number of Positions: 2

Centerline (Pitch): 2.2 mm [ .087 in ] Connector & Housing Type: Plug Operating Voltage: 100 VDC

## **Features**

### Product Type Features

Troduct Type readures	
Connector System	Board-to-Board
Connector & Housing Type	Plug
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	2
PCB Mount Orientation	Vertical
Electrical Characteristics	
Operating Voltage	100 VDC
Body Features	
Primary Product Color	Black
Contact Features	
Contact Mating Area Plating Material	Gold Flash
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	2 A



#### Mechanical Attachment

PCB Mount Retention	Without
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	LCP (Liquid Crystal Polymer)
Centerline (Pitch)	2.2 mm[.087 in]
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
UL Flammability Rating	UL 94V-0

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

#### Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



# Customers Also Bought












TE Part #1981061-1 LEAF BATTERY CONN W/B 3POS. P=3.2, PKG



TE Part #292331-3
BATTERY 3P SMT 1.6MM PITCH
ASSEMBLY CONN







### **Documents**

### **Product Drawings**

**BATTERY CONNECTOR ASSEMBLY** 

English

#### **CAD Files**

#### 3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_6337194-1\_B\_c-6337194-1-b.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_6337194-1\_B\_c-6337194-1-b.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_6337194-1\_B\_c-6337194-1-b.3d\_stp.zip

English

DC Jack Connectors, Board-to-Board, 2 Position, .087 in [2.2 mm] Centerline, Plug, 100 VDC, Vertical, Printed Circuit Board, Power & Signal



By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

# Datasheets & Catalog Pages

Products for Mobile Equipment

English

# **Product Specifications**

SMT BATTERY CONNECTOR 2 POSITION SURFACE MOUNT APPLICATION SPECIFICATION

English

**Application Specification** 

English