

ALR

TE Internal #: 636452-000

ANSI Street Lighting Photocells, Worldwide, Thermal, 420 – 530

VAC, Industrial / Commercial, 1800 VA Load Rating (Ballast),

Locking

View on TE.com >



Connectors > Lighting Connectors > Street Lighting Controls > ANSI Street Lighting Photocells



Product Availability: Worldwide

Street Lighting Photo Control Technology: Thermal

Operating Voltage Range: 420 – 530 VAC

Grade: Commercial, Industrial
Load Rating (Ballast): 1800 VA

Features

Product Type Features

r roduct Type reatures	
Light Sensor	CdS Photocell
Street Lighting Photo Control Technology	Thermal
Electrical Characteristics	
Operating Voltage Range	420 – 530 VAC
Load Rating (Ballast)	1800 VA
Load Rating (Tungsten)	1000 W
Fail Mode	On
Surge Protection	180 Joule
Operating Frequency	50 – 60 Hz
Body Features	
Compatible With Lamp Type	LED
Primary Product Color	Yellow
Mechanical Attachment	
Mounting Options	Locking
Housing Features	

High Impact Noryl with UV-Stabilized

Acrylic Window

Housing Material



Dimensions

Product Diameter	74 mm[2.93 in]
Product Height	50 mm[1.96 in]
Usage Conditions	
Operating Temperature Range	-40 - 65 °C[-40 - 149 °F]
Operation/Application	
Turn OFF Time Delay	30 – 45 seconds
Turn ON Light Level	1.5 fc
Turn ON Time Delay	30 – 45 seconds
Industry Standards	
Approved Standards	ANSI C136.10
Product Availability	
Product Availability	Worldwide
Packaging Features	
Packaging Quantity	6
Packaging Method	Box
Other	
Warranty	3 Years
Lighting Connector Comment	Dusk-to-dawn lighting control compatible with all solid state ballasts., Parking Lot, Security, & Street Lighting.
Grade	Commercial, Industrial

Product Compliance

OFF/ON Ratio

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) SVHC > Threshold:

5:1



Cd (.27% in Photo cell)

Article Safe Usage Statements:

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts























Customers Also Bought















Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_636452-000_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_636452-000_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_636452-000_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

M SERIES PHOTOCONTROL

English

ANSI Street Lighting Photocells, Worldwide, Thermal, 420 – 530 VAC, Industrial / Commercial, 1800 VA Load Rating (Ballast), Locking

