
# 640136-6 - ACTIVE

#### AMP

TE Internal #: 640136-6 Housing, Receptacle, Wire-to-Board, 6 Position, .156 in [3.96 mm] Centerline, 1 Row, Printed Circuit Board, Board Mount, -55 – 105 °C [-67 – 221 °F]

#### View on TE.com >

Connectors > PCB Connectors > Board-to-Board Connectors > Board-to-Board Connector Housings



#### Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 6

Centerline (Pitch): 3.96 mm [.156 in ]

Number of Rows: 1

### Features

#### **Product Type Features**

Connector & Housing Type

Connector System

Connector & Contact Terminates To

Receptacle

Wire-to-Board

Printed Circuit Board



#### **Configuration Features**

Number of Positions	6
Number of Rows	1
Contact Features	
Contact Type	Socket
Contact Current Rating (Max)	6 A
Mechanical Attachment	
Mating Alignment Type	Polarization
Mating Alignment	With
Connector Mounting Type	Board Mount
Housing Features	
Centerline (Pitch)	3.96 mm[.156 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

#### 640136-6

Housing, Receptacle, Wire-to-Board, 6 Position, .156 in [3.96 mm] Centerline, 1 Row, Printed Circuit Board, Board Mount, -55 – 105 °C [-67 – 221 °F]



#### **Operation/Application**

Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0

### **Product Compliance**


#### For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



TE Part # 3-61668-1 BIF-LEAF CONT CR/SNAP SN/BR

#### 640136-6

Housing, Receptacle, Wire-to-Board, 6 Position, .156 in [3.96 mm] Centerline, 1 Row, Printed Circuit Board, Board Mount, -55 – 105 °C [-67 – 221 °F]



## Customers Also Bought



### Documents

Product Drawings 06P EDGE CONN HSG, BIF-LEAF

English

CAD Files

#### 3D PDF

English

Customer View Model ENG\_CVM\_640136-6\_U.2d\_dxf.zip

English

Customer View Model ENG\_CVM\_640136-6\_U.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_640136-6\_U.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Bifurcated Leaf Contact

English

**Application Specification** 

English

Product Environmental Compliance MD\_640136-6\_05162018718\_dmtec

#### 640136-6

Housing, Receptacle, Wire-to-Board, 6 Position, .156 in [3.96 mm] Centerline, 1 Row, Printed Circuit Board, Board Mount, -55 – 105 °C [-67 – 221 °F]



English

MD\_640136-6\_05162018718\_dmtec

English

Instruction Sheets BIFURCATED LEAF CONTACT CONNECTORS

English

Instruction Sheet (U.S.)

English

Agency Approvals Agency Approval Document

English