

MTA 156

TE Internal #: 641937-2


Rectangular Power Connectors, Header, Plug, Wire-to-Board, 3 Position, 3.96 mm [.156 in] Centerline, Printed Circuit Board, UL 94V-

0, MTA 156

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: Header

Connector & Housing Type: Plug
Connector System: Wire-to-Board

Number of Positions: 3

Centerline (Pitch): 3.96 mm [.156 in]

Features

Product Type Features

Header Type	Partially Shrouded
Rectangular Power Connector Type	Header
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Loaded Positions	2
Number of Positions	3
PCB Mount Orientation	Vertical
Number of Power Positions	3
Number of Signal Positions	0
Number of Rows	1
Electrical Characteristics	

Electrical Characteristics



Operating Voltage	600 VAC
Contact Features	
Mating Post Length	10.16 mm[.4 in]
Contact Layout	Inline
Contact Mating Area Plating Material	Tin
Contact Underplating Material	Nickel
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	7 A
Contact Retention Within Housing	Without
Contact Type	Pin
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	2.54 μm[100 μin]
Termination Features	
Termination Post & Tail Length	3.7 mm[.146 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Strain Relief	Without
Mating Retention	With
Mating Alignment	Without
PCB Mount Alignment	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Retention Type	Friction Lock
Connector Mounting Type	Board Mount
Housing Features	
Centerline (Pitch)	3.96 mm[.156 in]
Housing Color	Natural
Housing Material	Thermoplastic Polyester
Dimensions	
Connector Height	10.8 mm
PCB Thickness (Recommended)	3.05 mm[.12 in]
Product Length	11.89 mm



Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
CSA Rating	Certified, LR 7189
UL Rating	Recognized
Agency/Standard	CSA, UL
Approved Standards	UL E28476
UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire
Packaging Features	
Packaging Quantity	3000
Packaging Method	Package
Other	

Product Compliance

Number of Blocked Positions

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products




will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts









Receptacle Housing: Wire-to-Board, with Mating Alignment, SL156

TE Part # 640251-3 03P SL156 HSG W/O RAMP NATL

TE Part # 3-644460-3 03P MTA156 CONN ASSY 18AWG ORA


03P MTA156 CONN ASSY 24AWG WHT



TE Part # 3-640427-3 03P MTA156 CONN ASSY 20AWG YEL



TE Part # 3-640599-3 03P MTA156 CONN ASSY 18AWG ORA



TE Part # 3-643821-3 03P MTA156 CONN ASSY 26AWG LF



TE Part # 3-640426-3 03P MTA156 CONN ASSY 18AWG ORA



TE Part # 3-643191-3 03P MTA156 CONN ASSY H/F 18AWG



TE Part # 3-644465-3 03P MTA156 CONN ASSY 18AWG



TE Part # 3-643817-3 03P MTA156 CONN ASSY 18AWG ORA



TE Part # 3-640600-3 03P MTA156 CONN ASSY 20AWG LF




TE Part # 643071-3 03P MTA156 FD-THRU COVER



TE Part # 3-640431-3 03P MTA156 CONN ASSY 18AWG ORA



TE Part # 3-640601-3 03P MTA156 CONN ASSY 22AWG LF



TE Part # 3-643819-3 03P MTA156 CONN ASSY 22AWG RED











Also in the Series MTA 156







PCB Connector Covers(88)



PCB Connector Keying(2)



PCB Connector Mounting(1)



PCB Headers & Receptacles(314)




Power Contacts(2)



Rectangular Power Connectors(698)



Standard Rectangular Connectors(337)



Customers Also Bought
























Documents

Product Drawings

03P MTA156 HDR ASSY SQ W/O#3

English

CAD Files

Customer View Model

ENG_CVM_CVM_641937-2_N.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_641937-2_N.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_641937-2_N.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Rectangular Power Connectors, Header, Plug, Wire-to-Board, 3 Position, 3.96 mm [. 156 in] Centerline, Printed Circuit Board, UL 94V-0, MTA 156



Agency Approvals

Agency Approval Document

English