MTA 156

TE Internal #: 644960-1

PCB Mount Header, Right Angle, Wire-to-Board, 18 Position, 3.96 mm [.156 in] Centerline, Partially Shrouded, Tin, Through Hole -

Solder, MTA 156


View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles











Connector System: Wire-to-Board

Number of Positions: 18

Number of Rows: 1

Centerline (Pitch): 3.96 mm [.156 in]
PCB Mount Orientation: Right Angle

Features

Product Type Features

Connector System	Wire-to-Board
Header Type	Partially Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header
Configuration Features	
Number of Columns	18
Number of Loaded Positions	14
Number of Positions	18
Number of Rows	1
PCB Mount Orientation	Right Angle
Electrical Characteristics	
Operating Voltage	600 VAC



Primary Product Color	Natural
Contact Features	
Contact Mating Area Length	10.16 mm[.4 in]
Mating Square Post Dimension	1.14 mm[.045 in]
PCB Contact Termination Area Plating Material Thickness	2.54 μm[100 μin]
Contact Layout	Inline
Contact Underplating Material Thickness	1.27 μm[50 μin]
Contact Mating Area Plating Material Thickness	2.54 μm[100 μin]
PCB Contact Termination Area Plating Material Finish	Matte
Contact Shape & Form	Square
Contact Mating Area Plating Material Finish	Matte
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Tin
Contact Type	Pin
Contact Current Rating (Max)	7 A
Termination Features	
Square Termination Post & Tail Dimension	1.14 mm[.045 in]
Termination Post & Tail Length	3.18 mm[.125 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Polarization
Mating Retention	With
Panel Mount Feature	Without
Mating Retention Type	Friction Lock
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	Without
Housing Features	
Right Angle Bending Side	Rear



Housing Material	Polyester - GF
Centerline (Pitch)	3.96 mm[.156 in]
Dimensions	
Connector Length	71.32 mm[2.808 in]
Connector Height	7.62 mm[.3 in]
Connector Width	17.88 mm[.704 in]
PCB Thickness (Recommended)	1.6 mm[.063 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Power
Circuit Application Industry Standards	Power
	Power CSA, UL
Industry Standards	
Industry Standards Agency/Standard	CSA, UL
Industry Standards Agency/Standard Approved Standards	CSA, UL CSA LR7189, UL E28476
Industry Standards Agency/Standard Approved Standards UL Flammability Rating	CSA, UL CSA LR7189, UL E28476
Industry Standards Agency/Standard Approved Standards UL Flammability Rating Packaging Features	CSA, UL CSA LR7189, UL E28476 UL 94V-0
Industry Standards Agency/Standard Approved Standards UL Flammability Rating Packaging Features Packaging Quantity	CSA, UL CSA LR7189, UL E28476 UL 94V-0
Industry Standards Agency/Standard Approved Standards UL Flammability Rating Packaging Features Packaging Quantity Packaging Type	CSA, UL CSA LR7189, UL E28476 UL 94V-0

Product Compliance

Number of Blocked Positions

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.

4



Solder Process Capability

Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




















Also in the Series MTA 156













PCB Headers & Receptacles(314)




Power Contacts(2)



Rectangular Power Connectors(698)



Standard Rectangular Connectors(337)



Customers Also Bought



IM41GR=IM RELAY 100mW 3V BIS



TE Part #0462-201-16141 SOC, SOLID, SIZE 16, 16-20AWG, NI




TE Part #179228-6
CRIMP TYPE II RECPT HSG



TE Part #745286-2 LATCHING BLOCK



TE Part #2-1419108-6 RTB14024F



TE Part #1217861-1 250 FASTON,PCB TAB,TCBR



TE Part #6-534237-4 16 MODII VRT SR CE 100/115





TE Part #644961-1 19P MTA156 HDR ASY WO4,8,12,16



Documents



Product Drawings

18P MTA156 HDR ASY WO4,8,12,16

English

CAD Files

Customer View Model

ENG_CVM_CVM_644960-1_C.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_644960-1_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_644960-1_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Agency Approvals

Agency Approval Document

English