

FASTON

TE Internal #: 66025-6


Quick Disconnects, Tab, 12 – 10 AWG Wire Size, 2.62 – 6.64 mm² Wire Size, 5180 – 13100 CMA Wire Size, Mating Tab Width 6.35 mm

[.25 in], Straight

View on TE.com >



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: Tab

Wire Size: 5180 – 13100 CMA

Mating Tab Width: 6.35 mm [.25 in]

Features

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Contact Features	
Quick Disconnect Terminal Type	Tab
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Copper Alloy
Terminal Plating Material	Tin
Crimp Type	Compression
Barrel Type	Closed
Termination Features	
Product Terminates To	Wire & Cable
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	



Product Length	27.94 mm[1.1 in]
Compatible Insulation Diameter Range	5.84 mm[.23 in]
Wire Size	5180 – 13100 CMA
Usage Conditions	
Insulation Option	Partially Insulated
Operating Temperature Range	105 °C[221 °F]
Packaging Features	
Packaging Quantity	50
Packaging Method	Box

Yellow

Product Compliance

Other

Barrel Color

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



Compatible Parts



Customers Also Bought


















Documents

Product Drawings
TAB,PIDG TERMI-BK 12-10

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_66025-6_R.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_66025-6_R.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_66025-6_R.3d_stp.zip

Quick Disconnects, Tab, 12 – 10 AWG Wire Size, 2.62 – 6.64 mm² Wire Size, 5180 – 13100 CMA Wire Size, Mating Tab Width 6.35 mm [.25 in], Straight



English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English