696423-3 - ACTIVE

PIDG

TE Internal #: 696423-3 Closed Ring Tongue Terminal, 16 – 14 AWG, #6 / M3.5 Stud Size, . 145 in Stud Diameter, Closed Barrel, Straight, Tin, Partially Insulated, PIDG

View on TE.com >

Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 2050 – 5180 CMA

Stud Size: #6, M3.5

Features

Product Type Features



Terminal Features	Sheared	
Ring Terminal Product Type	Closed Ring Tongue Terminal	
Stud Size	#6, M3.5	
Sealable	No	
Wire Insulation Support Retention Type	Insulation Support	
Configuration Features		
Number of Holes	1	
Body Features		
Product Weight	.934 g	
Insulation Sleeve Color	Natural	
Stripe Color	Blue	
Contact Features		
Barrel Type	Closed	
Terminal Orientation	Straight	
Terminal Plating Material	Tin	

Closed Ring Tongue Terminal, 16 – 14 AWG, #6 / M3.5 Stud Size, .145 in Stud Diameter, Closed Barrel, Straight, Tin, Partially Insulated, PIDG



Mechanical Attachment

Wire Insulation Support	With
Dimensions	
	.145 in
Wire Size	2050 – 5180 CMA
Tongue Thickness	.79 mm[.031 in]
Product Length	17.98 mm[.708 in]
Compatible Insulation Diameter (Max)	3.81 mm[.15 in]
Compatible Insulation Diameter Range	2.67 – 3.81 mm[.105 – .15 in]
Usage Conditions	
Insulation Option	Partially Insulated
Operating Temperature Range	150 °C[302 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin
Industry Standards	
Government Qualified Terminal	No

Packaging Features

Packaging Quantity	1000	
Packaging Method	Loose Piece	
Product Compliance For compliance documentation, visit the product page on TE.com>		
EU RoHS Directive 2011/65/EU	Compliant	
EU ELV Directive 2000/53/EC	Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC	
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.	
Solder Process Capability	Not applicable for solder process capability	

C For support call+1 800 522 6752


Closed Ring Tongue Terminal, 16 – 14 AWG, #6 / M3.5 Stud Size, .145 in Stud Diameter, Closed Barrel, Straight, Tin, Partially Insulated, PIDG



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




Also in the Series | PIDG


Compression Connectors(17)	Crimp Terminal Housings(1)	Crimp Wire Pins, Tabs & Ferrules(41)	Hand Crimping Tools(2)
		and the second second	
Knife Disconnects(11)	PCB Terminals(7)	Quick Disconnects(49)	Ring Terminals(611)

Closed Ring Tongue Terminal, 16 – 14 AWG, #6 / M3.5 Stud Size, .145 in Stud Diameter, Closed Barrel, Straight, Tin, Partially Insulated, PIDG





Customers Also Bought





ATUM-6/2-0-STK



Documents

Product Drawings TERMINAL, PIDG PVF2 R, 16-14, 6

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_696423-3_A.2d_dxf.zip

S For support call+1 800 522 6752

Closed Ring Tongue Terminal, 16 – 14 AWG, #6 / M3.5 Stud Size, .145 in Stud Diameter, Closed Barrel, Straight, Tin, Partially Insulated, PIDG



English

Customer View Model ENG_CVM_CVM_696423-3_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_696423-3_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages RADIATION_RESISTANT_PRE-INSULATED_TERMINALS_SPLICES

English

Product Specifications Application Specification

English