696426-1 - ACTIVE

PIDG

TE Internal #: 696426-1 Splices, Butt Splice, 24 – 20 AWG Wire Size, .2 – .6 mm² Wire Size, Serrated, .043 in [1.09 mm] Barrel Inside Diameter, 320 – 1290 CMA Wire Size, PIDG

View on TE.com >

Terminals & Splices > Splices



Wire Size: .2 – .6 mm²

Sealable: No

Splice Features: Serrated

Compatible Insulation Diameter Range: 2.54 mm [.04 – .1 in]

Features

Product Type Features



Splice Accessory Type	Splice	
Sealable	No	
Splice Type	Butt Splice	
Compatible With Discrete Wire Type	Stranded	
Wire Insulation Support Retention Type	Insulation Support	
Configuration Features		
Number of Serrations	8	
Compatible With Wire & Cable Type	Discrete Wire	
Body Features		
Insulation Type	Pre-Insulated	
Insulation Support Sleeve Material	Copper	
Stripe Color	White	
Insulation Material	PVF2	
Splice Features	Serrated	

Splices, Butt Splice, 24 – 20 AWG Wire Size, .2 – .6 mm² Wire Size, Serrated, .043 in [1.09 mm] Barrel Inside Diameter, 320 – 1290 CMA Wire Size, PIDG



Contact Features

Terminal Plating Material	Tin	
Contact Base Material	Copper	
Barrel Type	Closed	
Termination Features		
Termination Method to Wire & Cable	Crimp	
Mechanical Attachment		
Wire Insulation Support	With	
Dimensions		
Wire Size	320 – 1290 CMA	
Compatible Insulation Diameter Range	2.54 mm[.04 – .1 in]	
Barrel Inside Diameter	1.09 mm[.043 in]	
Product Length	26.29 mm[1.035 in]	
Usage Conditions		
Insulation Option	Fully Insulated	
Operating Temperature Range	150 °C[302 °F]	
Industry Standards		

Government Qualified Splice	No	
Packaging Features		
Packaging Quantity	1000	
Packaging Method	Loose Piece	
Product Compliance For compliance documentation, visit the product page on TE.com>		
EU RoHS Directive 2011/65/EU	Compliant	
EU ELV Directive 2000/53/EC	Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC	
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.	

C For support call+1 800 522 6752

Splices, Butt Splice, 24 – 20 AWG Wire Size, .2 – .6 mm² Wire Size, Serrated, .043 in [1.09 mm] Barrel Inside Diameter, 320 – 1290 CMA Wire Size, PIDG




Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts




Also in the Series | PIDG

Compression Connectors(17)	Crimp Terminal Housings(1)	Crimp Wire Pins, Tabs & Ferrules(41)	Hand Crimping Tools(2)
Knife Disconnects(11)	PCB Terminals(7)	Quick Disconnects(49)	Ring Terminals(607)

Splices, Butt Splice, 24 – 20 AWG Wire Size, .2 – .6 mm² Wire Size, Serrated, .043 in [1.09 mm] Barrel Inside Diameter, 320 – 1290 CMA Wire Size, PIDG





Customers Also Bought



AssyMinipak Hdl25s10pRARecptSc	MJ,TE,8P,COMPL.PIN,CAT5,PC	4551 1352 02	ACTUATOR,TYPE 1, SPARE PART PACK
TE Part #2336600-2			
ACTUATOR, TYPE 2, SPARE PART PACK			
Documents			

Product Drawings SPLICE BUTT PVF2 PIDG 24-20

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_696426-1_A.2d_dxf.zip

Splices, Butt Splice, 24 – 20 AWG Wire Size, .2 – .6 mm² Wire Size, Serrated, .043 in [1.09 mm] Barrel Inside Diameter, 320 – 1290 CMA Wire Size, PIDG



English

Customer View Model ENG_CVM_CVM_696426-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_696426-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages RADIATION_RESISTANT_PRE-INSULATED_TERMINALS_SPLICES

English

Product Specifications Application Specification

English