KRPA-14AY-24 V ACTIVE

Potter & Brumfield | Potter & Brumfield KRPA

TE Internal #: 7-1393104-8

Power Relays, Industrial Panel Plug-In, Monostable, AC, 2.02 VA Coil Power Rating AC, 85 Ω Coil Resistance, Potter & Brumfield

KRPA

View on TE.com >



Relays, Contactors & Switches > Relays > Power Relays



Power Relay Type: Industrial Panel Plug-In
Coil Magnetic System: Monostable, AC
Coil Power Rating Class: [2-3 VA]
Coil Power Rating AC: 2.02 VA

Coil Resistance: 85 Ω

Features

Product Type Features

Power Relay Type	Industrial Panel Plug-In
Electrical Characteristics	
Insulation Initial Dielectric Between Coil & Contact Class	500 – 1000 V
Insulation Initial Dielectric Between Contacts & Coil	1000 Vrms
Actuating System	AC
Insulation Initial Dielectric Between Open Contacts	1000 Vrms
Contact Limiting Making Current	10 A
Contact Limiting Short-Time Current	10 A
Contact Limiting Continuous Current	10 A
Insulation Initial Dielectric Between Adjacent Contacts	1000 Vrms
Insulation Initial Resistance	1000 ΜΩ
Contact Limiting Breaking Current	10 A
Coil Magnetic System	Monostable, AC
	2 – 3 VA
Coil Power Rating AC	2.02 VA
Coil Resistance	85 Ω
Coil Special Features	UL Coil Insulation Class B
Coil Voltage Rating	24 VAC



Contact Switching Load (Min)	100mA @ 12V
Contact Voltage Rating	240 VAC
Body Features	
Product Weight	85 g[2.988 oz]
	05 g[2.700 02]
Contact Features	
Contact Arrangement	3 Form C (CO)
Contact Current Class	5 – 10 A, 16 A
Contact Current Rating (Max)	10 A
Contact Material	Ag
Contact Number of Poles	3
Relay Terminal Type	Plug-In
Mechanical Attachment	
Relay Mounting Type	Socket
Dimensions	
Length Class (Mechanical)	35 – 40 mm
Length Class (Mechanical) Height Class (Mechanical)	35 – 40 mm 50 – 60 mm
Height Class (Mechanical)	50 – 60 mm
Height Class (Mechanical) Width Class (Mechanical)	50 – 60 mm 30 – 40 mm
Height Class (Mechanical) Width Class (Mechanical) Product Width	50 – 60 mm 30 – 40 mm 35.7 mm[1.405 in]
Height Class (Mechanical) Width Class (Mechanical) Product Width Product Length	50 – 60 mm 30 – 40 mm 35.7 mm[1.405 in] 35.7 mm[1.406 in]
Height Class (Mechanical) Width Class (Mechanical) Product Width Product Length Product Height	50 – 60 mm 30 – 40 mm 35.7 mm[1.405 in] 35.7 mm[1.406 in]
Height Class (Mechanical) Width Class (Mechanical) Product Width Product Length Product Height Usage Conditions	50 – 60 mm 30 – 40 mm 35.7 mm[1.405 in] 35.7 mm[1.406 in] 50.8 mm[2 in]
Height Class (Mechanical) Width Class (Mechanical) Product Width Product Length Product Height Usage Conditions Environmental Ambient Temperature Class	50 – 60 mm 30 – 40 mm 35.7 mm[1.405 in] 35.7 mm[1.406 in] 50.8 mm[2 in]
Height Class (Mechanical) Width Class (Mechanical) Product Width Product Length Product Height Usage Conditions Environmental Ambient Temperature Class Environmental Ambient Temperature (Max)	50 – 60 mm 30 – 40 mm 35.7 mm[1.405 in] 35.7 mm[1.406 in] 50.8 mm[2 in] 50 – 70 °C 55 °C[131 °F]
Height Class (Mechanical) Width Class (Mechanical) Product Width Product Length Product Height Usage Conditions Environmental Ambient Temperature Class Environmental Ambient Temperature (Max) Operating Temperature Range	50 – 60 mm 30 – 40 mm 35.7 mm[1.405 in] 35.7 mm[1.406 in] 50.8 mm[2 in] 50 – 70 °C 55 °C[131 °F]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold



EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts





Also in the Series | Potter & Brumfield KRPA





Customers Also Bought









Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_7-1393104-8_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_7-1393104-8_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_7-1393104-8_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

KRPA, KRP, KA, KR 5 to 10 Amp General Purpose Relay

English

Product Specifications

Definitions General Purpose Relays

English

Agency Approvals

UL

English