# V23057B0006A102 ~ ACTIVE

### SCHRACK | SCHRACK Power PCB Relay Card E

TE Internal #: 7-1393215-9 Power Relays, Standard, Monostable, DC, 480 mW Coil Power Rating DC, 1200 Ω Coil Resistance, 24 VDC Coil Voltage, SCHRACK Power PCB Relay Card E

#### View on TE.com >

### Relays, Contactors & Switches > Relays > Power Relays



Power Relay Type: Standard

Coil Magnetic System: Monostable, DC

Coil Power Rating DC: 480 mW

Coil Resistance: 1200  $\Omega$ 

Coil Voltage Rating: 24 VDC

### Features



### Product Type Features

Power Relay Type	Standard
Electrical Characteristics	
Coil Power Rating Class	400 – 500 mW
Coil Magnetic System	Monostable, DC
Coil Power Rating DC	480 mW
Coil Resistance	1200 Ω
Coil Voltage Rating	24 VDC
Contact Switching Voltage (Max)	400 VAC
Contact Voltage Rating	250 VAC
Body Features	
Product Weight	14 g[.494 oz]
Contact Features	
Contact Arrangement	1 Form A (NO)
Contact Current Class	2 – 5 A, 5 – 10 A

### V23057B0006A102

Power Relays, Standard, Monostable, DC, 480 mW Coil Power Rating DC, 1200  $\Omega$  Coil Resistance, 24 VDC Coil Voltage, SCHRACK Power PCB Relay Card E



Contact Current Rating (Max)	5 A
Contact Material	AgNi0.15
Contact Number of Poles	1
Relay Terminal Type	PCB-THT
Mechanical Attachment	
Relay Mounting Type	Printed Circuit Board
Dimensions	
Length Class (Mechanical)	25 – 30 mm
Height Class (Mechanical)	25 – 30 mm
Width Class (Mechanical)	10 – 11 mm
Product Width	10.4 mm[.405 in]
Product Length	28 mm[1.103 in]
Product Height	25.1 mm[.989 in]
Usage Conditions	
Environmental Ambient Temperature (Max)	70 °C[158 °F]
Operating Temperature Range	-40 – 70 °C[-40 – 158 °F]

### Packaging Features

## Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 260°C

Product Compliance Disclaimer

### V23057B0006A102

Power Relays, Standard, Monostable, DC, 480 mW Coil Power Rating DC, 1200  $\Omega$  Coil Resistance, 24 VDC Coil Voltage, SCHRACK Power PCB Relay Card E



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



Also in the Series | SCHRACK Power PCB Relay Card E



Power Relays	s(16)	

## **Customers Also Bought**



### V23057B0006A102

Power Relays, Standard, Monostable, DC, 480 mW Coil Power Rating DC, 1200  $\Omega$  Coil Resistance, 24 VDC Coil Voltage, SCHRACK Power PCB Relay Card E





## Documents

### **CAD** Files

### 3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_7-1393215-9\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_7-1393215-9\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_7-1393215-9\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use

Datasheets & Catalog Pages Power PCB Relay Card E

English

**Product Specifications** Definitions General Purpose Relays

English

Agency Approvals **VDE** Certificate

English