R10-E1P4-115V ~ ACTIVE

Potter & Brumfield | Potter & Brumfield R10

TE Internal #: 7-1393765-6

Power Relays, Industrial Panel Plug-In, Monostable, AC, 9000 Ω Coil


Resistance, 115 VAC Coil Voltage, 4 Form C (CO), Potter &

Brumfield R10

View on TE.com >



Relays, Contactors & Switches > Relays > Power Relays



Power Relay Type: Industrial Panel Plug-In
Coil Magnetic System: Monostable, AC

Coil Resistance: 9000 Ω

Coil Voltage Rating: 115 VAC

Contact Arrangement: 4 Form C (CO)

Features

Product Type Features

Product Type Features	
Power Relay Type	Industrial Panel Plug-In
Electrical Characteristics	
Insulation Initial Dielectric Between Coil & Contact Class	500 – 1000 V
Insulation Initial Dielectric Between Contacts & Coil	500 Vrms
Actuating System	AC
Insulation Initial Dielectric Between Open Contacts	500 Vrms
Insulation Initial Dielectric Between Adjacent Contacts	1000 Vrms
Insulation Initial Resistance	10000 ΜΩ
Coil Magnetic System	Monostable, AC
Coil Resistance	9000 Ω
Coil Voltage Rating	115 VAC
Contact Switching Load (Min)	0mA @ 0V
Contact Voltage Rating	120 VAC
Body Features	
Product Weight	40 g[1.41 oz]
Contact Features	
Contact Plating Material	Gold

Bifurcated/Twin Contacts

Contact Special Features



Contact Arrangement	4 Form C (CO)
Contact Current Class	2 – 5 A, 16 A
Contact Current Rating (Max)	3 A
Contact Material	Ag
Contact Number of Poles	4
Relay Terminal Type	Plug-In, Solder
Mechanical Attachment	
Relay Mounting Type	Socket
Dimensions	
Length Class (Mechanical)	25 – 30 mm
Height Class (Mechanical)	30 – 40 mm
Width Class (Mechanical)	16 – 20 mm
Product Width	18.7 mm[.736 in]
Product Length	24.1 mm[.949 in]
Product Height	30.2 mm[1.189 in]
Usage Conditions	
Environmental Ambient Temperature Class	70 – 85 °C
Environmental Ambient Temperature (Max)	75 °C[167 °F]
Operating Temperature Range	-55 – 75 °C
Packaging Features	
Packaging Method	Package

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU EU ELV Directive 2000/53/EC Not Compliant China RoHS 2 Directive MIIT Order No 32, 2016 EU REACH Regulation (EC) No. 1907/2006 Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 202 (233) SVHC > Threshold:
China RoHS 2 Directive MIIT Order No 32, 2016 EU REACH Regulation (EC) No. 1907/2006 Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 202 (233) SVHC > Threshold:
EU REACH Regulation (EC) No. 1907/2006 Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 202 (233) SVHC > Threshold:
(235) Candidate List Declared Against: JAN 202 (233) SVHC > Threshold:
Pb (3.7% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.



Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1-1393143-2 27E129=SOCKET,R10,16,PC,PHEN



TE Part # 1393143-9 27E126=SOCKET,R10,16,SLG,PHE



TE Part # 1-1393143-5 27E152=SOCKET,R10,ASSY,W/BRK



TE Part # 2-1393143-2 27E194=SOCKET,R10,16,PC,PHEN



27E213=SOCKET,R10,16,PC,PHEN



TE Part # 4-1393143-4 27E461=SOCKETS



TE Part # 5-1393143-1 27E637=SOCKETS



TE Part # 4-1393143-8 27E629=SOCKETS

Also in the Series | Potter & Brumfield R10






PCB Headers & Receptacles(1)



Power Relays(180)



Customers Also Bought















Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_7-1393765-6_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_7-1393765-6_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_7-1393765-6_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

R10 General Purpose Dry Circuit to 7.5 Amp Multicontact AC or DC Relay

English

Power Relays, Industrial Panel Plug-In, Monostable, AC, 9000 Ω Coil Resistance, 115 VAC Coil Voltage, 4 Form C (CO), Potter & Brumfield R10



Product Specifications

Definitions General Purpose Relays

English

Agency Approvals

CSA Certificate

English