7-1735480-4 - ACTIVE

Free Height

TE Internal #: 7-1735480-4 PCB Mount Receptacle, Vertical, Board-to-Board, 100 Position, .8 mm [.031 in] Centerline, Gold, Surface Mount, Signal, Natural, Free Height

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > Free Height Receptacle Conn: Board-Board, Vertical, 100, 0.8mm



PCB Connector Assembly Type: PCB Mount Receptacle

PCB Mount Orientation: Vertical

Connector System: Board-to-Board

Number of Positions: 100

Centerline (Pitch): .8 mm [.031 in]

All Free Height Receptacle Conn: Board-Board, Vertical, 100, 0.8mm (24)

Features

Product Type Features

PCB Connector Assembly Type

Connector System

PCB Mount Receptacle

Board-to-Board

Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Stackable	Yes
PCB Mount Orientation	Vertical
Number of Positions	100
Board-to-Board Configuration	Parallel
Electrical Characteristics	
Dielectric Withstanding Voltage (Max)	500 VAC
Insulation Resistance	2 MΩ
Operating Voltage	100 VAC
Body Features	
Primary Product Color	Natural
Contact Features	

PCB Mount Receptacle, Vertical, Board-to-Board, 100 Position, .8 mm [.031 in] Centerline, Gold, Surface Mount, Signal, Natural, Free Height



PCB Contact Termination Area Plating Material Thickness	2 μm[78.74 μin]	
Contact Layout	Inline	
Mating Tab Width	.4 mm[.016 in]	
Mating Tab Thickness	.2 mm[.008 in]	
PCB Contact Termination Area Plating Material Finish	Matte	
PCB Contact Termination Area Plating Material	Tin	
Contact Base Material	Copper Alloy	
Contact Mating Area Plating Material	Gold	
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]	
Contact Type	Socket	
Contact Current Rating (Max)	.5 A	
Termination Features		
Rectangular Termination Post & Tail Thickness	.2 mm[.008 in]	
Rectangular Termination Post & Tail Width	.3 mm[.012 in]	
Termination Method to Printed Circuit Board	Surface Mount	
Mechanical Attachment		
Mounting Alignment Feature Length	.5 mm[.02 in]	
PCB Mount Alignment Type	Positioning Bosses	
Mating Alignment	With	
Mating Alignment Type	Polarization	
PCB Mount Retention	Without	
PCB Mount Alignment	With	
Connector Mounting Type	Board Mount	
Housing Features		
Mating Entry Location	Тор	
Centerline (Pitch)	.8 mm[.031 in]	
Housing Material	Matte	
Dimensions		
Connector Height	17 mm[.669 in]	
Stack Height	17 mm, 18 mm, 19 mm, 20 mm[.669 in][.709 in][.748 in][.787 in]	
Usage Conditions		
Housing Temperature Rating	High	

C For support call+1 800 522 6752

PCB Mount Receptacle, Vertical, Board-to-Board, 100 Position, .8 mm [.031 in] Centerline, Gold, Surface Mount, Signal, Natural, Free Height



Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Operation/Application	
Assembly Process Feature	None
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
	.5 in
Packaging Quantity	10
Packaging Type	Box, Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023

(235)Candidate List Declared Against: JUNE2023 (235)Does not contain REACH SVHC

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Halogen Content

Reflow solder capable to 260°C

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts


C For support call+1 800 522 6752

PCB Mount Receptacle, Vertical, Board-to-Board, 100 Position, .8 mm [.031 in] Centerline, Gold, Surface Mount, Signal, Natural, Free Height





Also in the Series | Free Height



PCB Headers & Receptacles(759)

Customers Also Bought







=TE



	1,1377		
TE Part #3-5177986-2 0.8FH,P08H.5,060,08/Sn,TR,SC	TE Part #87224-6 06 MODII HDR SRST UNSHRD .100	TE Part #130005 PIDG R 22-16 10 (5MM)	TE Part #102241-2 04 MODIV HG COMP SR .100 POL

TE Part #2311768-1

THREADED

AMPL REC, HD22, R/A, 26P,

=TE

TE Part #ZPF00000000018784

FDBA 50H 24-61 PY-K-C276

Documents

TE Part #1625854-3

0603 PROBE PAD

Product Drawings 0.8FH,R17H.5,100,30/Sn,TU

English

CAD Files Customer View Model ENG_CVM_CVM_7-1735480-4_A.2d_dxf.zip

PCB Mount Receptacle, Vertical, Board-to-Board, 100 Position, .8 mm [.031 in] Centerline, Gold, Surface Mount, Signal, Natural, Free Height



English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_7-1735480-4_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_7-1735480-4_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Product Specification

English

Product Specification

English