RP73PF1E7K15BTDF <

Holsworthy | Holsworthy RP73

TE Internal #: 7-2176311-7 7.15K Ω, Thin Film, Precision Resistor, .1 %, 2 Termination, 0402, Taped & Reeled, .1 W, ±25 ppm/°C, Solder, 1 x .5 x .3 mm, Holsworthy RP73

View on TE.com >





Resistor Type: Precision Resistor

Number of Terminations: 2

Package Size Code: 0402

Packaging Method: Taped & Reeled

Passive Component Tolerance: .1 %

Features



Product Type Features

Product Type	Fixed Resistor
Resistor Type	Precision Resistor
Package Size Code	0402
Element Type	Thin Film
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Voltage Rating	25 V
Passive Component Tolerance	.1 %
Resistance Class	$1k\Omega - 1M\Omega$
Resistance Value	7.15Κ Ω
Power Rating	.1 W
Termination Features	
Number of Terminations	2

RP73PF1E7K15BTDF

7.15K Ω, Thin Film, Precision Resistor, .1 %, 2 Termination, 0402, Taped & Reeled, .1 W, ±25 ppm/°C, Solder, 1 x .5 x .3 mm, Holsworthy RP73



Surface Mount Resistor Termination Type	Solder
Dimensions	
Passive Component Dimensions	1 x .5 x .3 mm
Usage Conditions	
Operating Temperature Range	-55 – 155 °C
Temperature Coefficient	±25 ppm/°C
Packaging Features	
Packaging Method	Taped & Reeled
Product Compliance For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU	Compliant
FUELV/Directive 2000/E2/EC	
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Compliant No Restricted Materials Above Threshold

Does not contain REACH SVHC

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

RP73PF1E7K15BTDF

7.15K Ω , Thin Film, Precision Resistor, .1 %, 2 Termination, 0402, Taped & Reeled, .1 W, ±25 ppm/°C, Solder, 1 x .5 x .3 mm, Holsworthy RP73








Also in the Series | Holsworthy RP73



Surface Mount Resistors(4556)



Customers Also Bought



RP73PF1E7K15BTDF

7.15K Ω, Thin Film, Precision Resistor, .1 %, 2 Termination, 0402, Taped & Reeled, .1 W, ±25 ppm/°C, Solder, 1 x .5 x .3 mm, Holsworthy RP73





Documents

Product Drawings RP 1E 0.1W 7K15 0.1% 25PPM 1K RL

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_7-2176311-7_BA.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_7-2176311-7_BA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_7-2176311-7_BA.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages RP73-0915

English