TE Internal #: 770565-2

TE Internal Description: MINI AMP-IN 22-18 AWG SNPB/PHBZ

View on TE.com >



Terminals & Splices > PCB Terminals











PCB Terminal Type: PCB Pin

PCB Thickness (Recommended): 1.57 mm [.062 in]

PCB Hole Diameter: 1.83 mm [.072 in]

Profile Height from PCB: 1.73 mm [.068 in]

Compatible Insulation Diameter (Max): 2.79 mm [.11 in]

Features

Product Type Features

Terminal Features	Stud Hole
Contact Features	
Terminal Plating Finish	Bright
Contact Mating Area Plating Material Thickness	4 μm[157.48 μin]
PCB Terminal Type	PCB Pin
Terminal Size	Miniature
Terminal Orientation	Straight
Termination Features	
Product Terminates To	Printed Circuit Board
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
	2.20
Extension Below Board	2.29 mm[.09 in]

1.83 mm[.072 in]

PCB Hole Diameter



Compatible Insulation Diameter (Max) Compatible Insulation Diameter Range 1.52 – 2.79 mm[.06 – .11 in] Wire Size .3 – .9 mm² Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Packaging Features Packaging Quantity 7000 Reel Other Terminals & Splices Comment Machine applied applicator required., No hand tools available in loose piece.	Profile Height from PCB	1.73 mm[.068 in]
Wire Size Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Packaging Features Packaging Quantity 7000 Packaging Method Reel Other Terminals & Splices Comment Machine applied applicator required., No hand tools available., Not available in loose	Compatible Insulation Diameter (Max)	2.79 mm[.11 in]
Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Packaging Features Packaging Quantity 7000 Packaging Method Reel Other Terminals & Splices Comment Machine applied applicator required., No hand tools available in loose	Compatible Insulation Diameter Range	1.52 – 2.79 mm[.06 – .11 in]
Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Packaging Features Packaging Quantity 7000 Packaging Method Reel Other Terminals & Splices Comment Machine applied applicator required., No hand tools available., Not available in loose	Wire Size	.3 – .9 mm²
Packaging Features Packaging Quantity Packaging Method Reel Other Terminals & Splices Comment Machine applied applicator required., No hand tools available in loose	Usage Conditions	
Packaging Quantity Packaging Method Reel Other Terminals & Splices Comment Machine applied applicator required., No hand tools available in loose	Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Packaging Method Cother Terminals & Splices Comment Machine applied applicator required., No hand tools available in loose	Packaging Features	
Other Terminals & Splices Comment Machine applied applicator required., No hand tools available., Not available in loose	Packaging Quantity	7000
Terminals & Splices Comment Machine applied applicator required., No hand tools available., Not available in loose	Packaging Method	Reel
hand tools available., Not available in loose	Other	
	Terminals & Splices Comment	hand tools available., Not available in loose

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



Customers Also Bought













Documents

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_770565-2_H1.3d_igs.zip

English

Customer View Model

ENG_CVM_770565-2_H1.3d_stp.zip

English

Customer View Model

ENG_CVM_770565-2_H1.2d_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

