
794956-3 • ACTIVE

VAL-U-LOK

TE Internal #: 794956-3 Power Contacts, Contact, 600 VAC, Tin, 22 – 18 AWG Wire Size, .3 – .82 mm² Wire Size, Wire & Cable, Crimp, Power, Socket, -40 – 105 ° C [-40 – 221 °F]

View on TE.com >

Connectors > Power Connectors > Power Contacts



Power Contact Type: **Contact** Operating Voltage: **600 VAC** Contact Mating Area Plating Material: **Tin**

Wire Size: .3 – .82 mm²

Features

Product Type Features



Froduct Type reatures	
Power Contact Type	Contact
Connector & Contact Terminates To	Wire & Cable
Electrical Characteristics	
Operating Voltage	600 VAC
Contact Features	
Contact Shape & Form	Single Beam
Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	9 A
Contact Type	Socket
Contact Retention Within Housing	With
Mating Square Post Dimension	1.14 mm[.045 in]
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material Thickness	2.54 μm[100 μin]
Wire Contact Termination Area Plating Thickness	2.54 μm[100 μin]
Wire Contact Termination Area Plating Material	Pre-Tin

Power Contacts, Contact, 600 VAC, Tin, 22 – 18 AWG Wire Size, .3 – .82 mm² Wire Size, Wire & Cable, Crimp, Power, Socket, -40 – 105 °C [-40 – 221 °F]



Wire Contact Termination Area Plating Material Finish	Bright
Contact Orientation	Straight
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Wire Size	.3 – .82 mm²
Compatible Insulation Diameter Range	1.5 – 3.1 mm[.059 – .122 in]
Usage Conditions	
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
CSA Rating	208567
UL Rating	Recognized
Agency/Standard	CSA, UL
Packaging Features	

Packaging Quantity	3500
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Power Contacts, Contact, 600 VAC, Tin, 22 – 18 AWG Wire Size, .3 – .82 mm² Wire Size, Wire & Cable, Crimp, Power, Socket, -40 – 105 °C [-40 – 221 °F]



Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # 5-2151096-1 OCEAN-2.0-APPLICATOR-S-062F125F



TE Part # 5-2151096-2 OCEAN-2.0-APPLICATOR-S-062F125FA



TE Part # 7-2151096-1 OCEAN-2.0-APPLICATOR-S-062F125F



TE Part # 7-2151096-2 OCEAN-2.0-APPLICATOR-S-062F125FA



Customers Also Bought

Power Contacts, Contact, 600 VAC, Tin, 22 – 18 AWG Wire Size, .3 – .82 mm² Wire Size, Wire & Cable, Crimp, Power, Socket, -40 – 105 °C [-40 – 221 °F]





Documents

Product Drawings VAL-U-LOK SKT PHBZ SN 22-18AWG

English

CAD Files Customer View Model

ENG_CVM_CVM_794956-3_G.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_794956-3_G.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_794956-3_G.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

English

Product Specifications

Application Specification

English

Product Environmental Compliance Product Compliance Document

Power Contacts, Contact, 600 VAC, Tin, 22 – 18 AWG Wire Size, .3 – .82 mm² Wire Size, Wire & Cable, Crimp, Power, Socket, -40 – 105 °C [-40 – 221 °F]



English

Product Compliance Document

English