

PIDG

TE Internal #: 8-1377174-0


Quick Disconnects, Receptacle, 22 – 15 AWG Wire Size, .3 – 1.5 mm² Wire Size, 592 – 2960 CMA Wire Size, Mating Tab Width 2.8

mm [.11 in], PIDG

View on TE.com >



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: Receptacle

Wire Size: **592 – 2960 CMA**

Mating Tab Width: 2.8 mm [.11 in]

Features

Product Type Features

Insertion Force	Normal
Electrical Characteristics	
Voltage Rating	300 V
Body Features	
Insulation Material	Nylon
Contact Features	
Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.41 mm[.016 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	Compression
Barrel Type	Closed
Mechanical Attachment	



Wire Insulation Support	With
Mating Retention Type	Dimple
Dimensions	
Compatible Insulation Diameter Range	3.5 mm[.14 in]
Wire Size	592 – 2960 CMA
Usage Conditions	
Insulation Option	Partially Insulated
Operating Temperature Range	105 °C[221 °F]
Packaging Features	
Packaging Quantity	50
Packaging Method	Box
Other	
Barrel Color	Red

Bulk number 165564-1.

Product Compliance

Terminals & Splices Comment

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought





Documents

Product Drawings

SMP 0-0165564-1

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_8-1377174-0_C1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_8-1377174-0_C1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_8-1377174-0_C1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

RADIATION_RESISTANT_PRE-INSULATED_TERMINALS_SPLICES

English

Product Specifications

Application Specification

English