KUHP-5AT1-120 ✓ ACTIVE

Potter & Brumfield | Potter & Brumfield KUHP

TE Internal #: 8-1393114-1

Power Relays, Industrial Panel Plug-In, Monostable, AC, 2.9 VA Coil Power Rating AC, 1700 Ω Coil Resistance, Potter & Brumfield KUHP

View on TE.com >



Relays, Contactors & Switches > Relays > Power Relays



Power Relay Type: Industrial Panel Plug-In
Coil Magnetic System: Monostable, AC
Coil Power Rating Class: [2-3 VA]
Coil Power Rating AC: 2.9 VA

Coil Resistance: 1700 Ω

Features

Product Type Features

Power Relay Type	Industrial Panel Plug-In
Electrical Characteristics	
Insulation Initial Dielectric Between Coil & Contact Class	3500 – 4000 V
Insulation Initial Dielectric Between Contacts & Coil	3750 Vrms
Actuating System	AC
Insulation Initial Dielectric Between Open Contacts	1200 Vrms
Contact Limiting Making Current	30 A
Contact Limiting Short-Time Current	30 A
Contact Limiting Continuous Current	30 A
Insulation Initial Dielectric Between Adjacent Contacts	3750 Vrms
Insulation Initial Resistance	100 ΜΩ
Contact Limiting Breaking Current	30 A
Coil Magnetic System	Monostable, AC
	2 – 3 VA
Coil Power Rating AC	2.9 VA
Coil Resistance	1700 Ω
Coil Special Features	UL Coil Insulation Class B
Coil Voltage Rating	120 VAC
Contact Switching Load (Min)	300mA @ 12V



Contact Voltage Rating	240 VAC
Body Features	
Product Weight	92 g[3.245 oz]
Contact Features	
Contact Arrangement	1 Form C (CO)
Contact Current Class	16 A, 20 – 30 A
Contact Current Rating (Max)	30 A
Contact Material	AgCdO
Contact Number of Poles	1
Relay Terminal Type	Quick Connect, Solder
Mechanical Attachment	
Relay Mounting Type	Flange Mount, Panel Mount
Dimensions	
Length Class (Mechanical)	35 – 40 mm
Width Class (Mechanical)	30 – 40 mm
Product Width	35.4 mm[1.394 in]
Product Width	35.4 mm[1.394 in]
Product Width Product Length	35.4 mm[1.394 in] 38.1 mm[1.5 in]
Product Width Product Length Product Height	35.4 mm[1.394 in] 38.1 mm[1.5 in]
Product Width Product Length Product Height Usage Conditions	35.4 mm[1.394 in] 38.1 mm[1.5 in] 62.5 mm[2.461 in]
Product Width Product Length Product Height Usage Conditions Environmental Ambient Temperature Class	35.4 mm[1.394 in] 38.1 mm[1.5 in] 62.5 mm[2.461 in] 0 – 50 °C
Product Width Product Length Product Height Usage Conditions Environmental Ambient Temperature Class Environmental Ambient Temperature (Max)	35.4 mm[1.394 in] 38.1 mm[1.5 in] 62.5 mm[2.461 in] 0 – 50 °C 45 °C[113 °F]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)



Candidate List Declared Against: JAN 2023 (233)

SVHC > Threshold:

Cadmium oxide (10% in Component Part)
Article Safe Usage Statements:

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per
homogenous material. Also BFR/CFR/PVC
Free

Solder Process Capability

Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Potter & Brumfield KUHP



Customers Also Bought

09/20/2023 08:26PM | Page 3



















Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_8-1393114-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_8-1393114-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_8-1393114-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

KUHP 30 Amp Power Relays

English

Product Specifications

Definitions General Purpose Relays

English

Agency Approvals

UL

English