Buchanan

TE Internal #: 8-1437652-6 Barrier Strips, Tri-Barrier, Printed Circuit Pin, Wire-to-Board, 5 Position, 9.53 mm [.375 in] Centerline, 1 Row, Operating Voltage 300 V / 600 V

View on TE.com >

Connectors > Terminal Blocks & Strips > Barrier Strips



Barrier Strip Style: Tri-Barrier
Bottom Termination Type: Printed Circuit Pin
Connector System: Wire-to-Board
Number of Positions: 5

Centerline (Pitch): 9.53 mm [.375 in]

Features



Product Type Features

Block Style	Flat Bottom with standoffs
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Levels	1
Number of Positions	5
Number of Rows	1
Electrical Characteristics	
Operating Voltage	300 V, 600 V
Body Features	
Primary Product Color	Black
Product Orientation	Vertical
Barrier Strip Style	Tri-Barrier

8-1437652-6

Barrier Strips, Tri-Barrier, Printed Circuit Pin, Wire-to-Board, 5 Position, 9.53 mm [.375 in] Centerline, 1 Row, Operating Voltage 300 V / 600 V



Contact Features

PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	5 A, 25 A
Termination Features	
Bottom Termination Type	Printed Circuit Pin
Mechanical Attachment	
Screw Plating Material	Zinc Chromate
Screw Material	Steel
Top Termination Type	Binding Combo Head
Mounting Options	None
Thread Size	6-32
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Thermoplastic
Centerline (Pitch)	9.53 mm[.375 in]

Dimensions

Product Length		49.17 mm[1.936 in]
Wire Size		.3 – 3 mm²
Usage Conditions		
Operating Temperatu	ire Range	0-105 °C[0-221 °F]
Operation/Application		
Circuit Application		Power
Industry Standards		
UL Flammability Ratin	9	UL 94V-0
Other		
Terminal Blocks & Stri	ips Comment	Other options available upon request, consult our Product Information Center.
Product Compliance For compliance documentation	Ə n, visit the product page on TE.com>	
EU RoHS Directive 20	11/65/EU	Compliant

C For support call+1 800 522 6752

8-1437652-6

Barrier Strips, Tri-Barrier, Printed Circuit Pin, Wire-to-Board, 5 Position, 9.53 mm [.375 in] Centerline, 1 Row, Operating Voltage 300 V / 600 V



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought



8-1437652-6

Barrier Strips, Tri-Barrier, Printed Circuit Pin, Wire-to-Board, 5 Position, 9.53 mm [.375 in] Centerline, 1 Row, Operating Voltage 300 V / 600 V





Documents

Product Drawings 6PCV-05-1341=#6 TRIBARRIER - S

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_8-1437652-6_P.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_8-1437652-6_P.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_8-1437652-6_P.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages BUCHANAN TERMINAL BLOCKS CATALOG - BARRIER STRIPS

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English