

### SOLISTRAND

TE Internal #: 8-33466-3 Closed Ring Tongue Terminal, 6 AWG, M8 / 5/16 Stud Size, 8.33 mm [.328 in] Stud Diameter, Closed Barrel, Straight, Tin, Uninsulated

#### View on TE.com >

Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 20800 - 33100 CMA

Stud Size: 5/16, M8

# Features

## **Product Type Features**

Ring Terminal Product Type	Closed Ring Tongue Terminal				
Stud Size	5/16, M8				
Sealable	No				
Wire Insulation Support Retention Type	Non-Insulation Support				
Configuration Features					
Number of Holes	1				
Body Features					
Product Weight	6.343 g				
Contact Features					
Barrel Type	Closed				
Terminal Orientation	Straight				
Terminal Plating Material	Tin				
Mechanical Attachment					
Wire Insulation Support	Without				
Dimensions					



### 8-33466-3

Closed Ring Tongue Terminal, 6 AWG, M8 / 5/16 Stud Size, 8.33 mm [.328 in] Stud Diameter, Closed Barrel, Straight, Tin, Uninsulated



Wire Size	20800 – 33100 CMA			
Stud Diameter	8.33 mm[.328 in]			
Tongue Thickness	1.45 mm[.057 in]			
Product Length	31.65 mm[1.246 in]			
Barrel Inside Diameter	5.89 mm[.232 in]			
Usage Conditions				
Insulation Option	Uninsulated			
Operating Temperature Range	170 °C[338 °F]			
Operation/Application				
Compatible With Wire Base Material	Copper			
Compatible With Wire Plating Material	Tin			
Industry Standards				
Government Qualified Terminal	No			
Packaging Features				
Packaging Quantity	25			

# Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant		
EU ELV Directive 2000/53/EC	Compliant		
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold		
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC		
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free		
Solder Process Capability	Not applicable for solder process capability		

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these

## 8-33466-3

Closed Ring Tongue Terminal, 6 AWG, M8 / 5/16 Stud Size, 8.33 mm [.328 in] Stud Diameter, Closed Barrel, Straight, Tin, Uninsulated



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



# Customers Also Bought



POWERBAND CONT ASSY, SILVER PLT	CABLE GRIP,SZ 17,CPC	250 FASTON TAB TPBR	RING TERMINAL 22-18 AWG TPBR
Reverse to the second s		ETE	THE REPORT OF TH
TE Part #6-1437624-9 PKG90B1/4=KNOB PLASTIC 1/4 LEX	TE Part #1924487-1 MOUNTING CLIP, AMPSEAL 16	TE Part #324061 TERMINAL,SOLIS R 8 8	TE Part #7-1618401-3 LEV200A4NAF01=Contactor, w/Coil Sup

TE Part #1520230-2 7402K4=20 AMP TOGGLE

## Documents

### 8-33466-3

Closed Ring Tongue Terminal, 6 AWG, M8 / 5/16 Stud Size, 8.33 mm [.328 in] Stud Diameter, Closed Barrel, Straight, Tin, Uninsulated



# Product Drawings

TERMINAL, SOLIS R 6 5/16

English

# **CAD** Files

Customer View Model

# ENG\_CVM\_CVM\_8-33466-3\_AP.2d\_dxf.zip

English

3D PDF

3D

Customer View Model ENG\_CVM\_CVM\_8-33466-3\_AP.3d\_igs.zip

English

Customer View Model

### ENG\_CVM\_CVM\_8-33466-3\_AP.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

# Datasheets & Catalog Pages SOLISTRAND - QRG

English

### RADIATION\_RESISTANT\_PRE-INSULATED\_TERMINALS\_SPLICES

English