805M1-0200-01 ~ ACTIVE

MEAS | MEAS 805 TE Internal #: 805M1-0200-01 AC Response Embedded Accelerometers, Uniaxial Sensing, MEAS 805

View on TE.com >

Sensors > Vibration Sensors



Accelerometer Type: 3-Wire Voltage

Vibration Sensor Product Type: AC Response Embedded Accelerometers

Number of Sensing Axes: Uniaxial

Frequency Response: 1 to 8000 Hz

Full Scale Output Voltage: ±2 VDC

Features

Product Type Features

Accelerometer Type

Vibration Sensor Product Type

E

3-Wire Voltage

AC Response Embedded Accelerometers

Electrical Characteristics

| Excitation Voltage | 3 – 5.5 VDC | | | | | | | | |
|-----------------------------|----------------------------|--|--|--|--|--|--|--|--|
| Full Scale Output Voltage | ±2 VDC | | | | | | | | |
| Signal Characteristics | | | | | | | | | |
| Frequency Response | 1 to 8000 Hz | | | | | | | | |
| Body Features | | | | | | | | | |
| Product Weight | 5 g[.17 oz] | | | | | | | | |
| Primary Product Material | Stainless Steel | | | | | | | | |
| Number of Sensing Axes | Uniaxial | | | | | | | | |
| Mechanical Attachment | | | | | | | | | |
| Mounting Type | Screw Mount | | | | | | | | |
| Usage Conditions | | | | | | | | | |
| Operating Temperature Range | -40 - 100 °C[-40 - 212 °F] | | | | | | | | |
| Other | | | | | | | | | |
| Nonlinearity | ±1 %FSO | | | | | | | | |
| | | | | | | | | | |

805M1-0200-01

AC Response Embedded Accelerometers, Uniaxial Sensing, MEAS 805



| Acceleration Range (±) | 200 g | | | |
|---|--|--|--|--|
| Sensitivity | 10 mV/g | | | |
| Product Compliance For compliance documentation, visit the product page on TE.com> | | | | |
| EU RoHS Directive 2011/65/EU | Compliant | | | |
| EU ELV Directive 2000/53/EC | Not Yet Reviewed | | | |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold | | | |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUN 2020 (209) Does not contain REACH SVHC | | | |
| Halogen Content | Not Yet Reviewed for halogen content | | | |
| Solder Process Capability | Not reviewed for solder process capability | | | |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | MEAS 805

C For support call+1 800 522 6752

805M1-0200-01

AC Response Embedded Accelerometers, Uniaxial Sensing, MEAS 805





Customers Also Bought



| SlimSeal Miniature Receptacles | Pt1000, 1.2x4.0, Class A, PTFM102A1A0 | TERMI-BLOK PCB SIDE ENTRY STAC | Antenna 1/4 Wave Whip 433MHz SMA |
|--------------------------------|---------------------------------------|--------------------------------|----------------------------------|
| | | | |
| | | | |

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_805M1-0200-01_M.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_805M1-0200-01_M.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_805M1-0200-01_M.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

805M1_Accelerometer

English

805M1-0200-01

AC Response Embedded Accelerometers, Uniaxial Sensing, MEAS 805

