

MEAS | MEAS 86 Series TE Internal #: 86-300G-R TE Internal Description: 300 PSIG RIBBON CABLE MV PRESSURE SENSOR MV Output Pressure Sensor, 16 mm

#### View on TE.com >

Sensors > Pressure Sensors > Media Isolated Pressure Sensors > MV Output Pressure Sensor, 16 mm



Pressure: [300 psi]

Media Isolated Pressure Sensor Type: Media Isolated mV Output Pressure Sensors

Media Isolated Pressure Sensor Style: Gauge

Output/Span: 100mV

Operating Temperature Range: -40 – 125 °C [-40 – 257 °F]

### All MV Output Pressure Sensor, 16 mm (30)

### Features

### **Product Type Features**

Media Isolated Pressure Sensor Type



Media Isolated mV Output Pressure Sensors

Media Isolated Pressure Sensor Style	Gauge				
Configuration Features					
Electrical Connection	Ribbon Cable				
Electrical Characteristics					
Supply Current	1.5 mA				
Dimensions					
Dimensions	Dia 15.82 x 11.4 mm[Dia .622 x .448 in]				
Usage Conditions					
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]				
Operation/Application					
Proof Pressure Range	3X				
	300 psi				
Output/Span	100mV				
Packaging Features					
Operating Temperature Range Operation/Application Proof Pressure Range Output/Span	3X 300 psi				

**C** For support call+1 800 522 6752

08/22/2023 04:30AM | Page 1

#### 300 PSIG RIBBON CABLE MV PRESSURE SENSOR



Media Isolated Pressure Sensor Package	O-Ring Mount
Other	
Non-Linearity	± .1 %
Sensor Options	No Tube
Product Compliance	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**




# Also in the Series | MEAS 86 Series

**C** For support call+1 800 522 6752

### 300 PSIG RIBBON CABLE MV PRESSURE SENSOR





# **Customers Also Bought**



	40CMH2O GAUGE SENSOR	DBL400	PRESS XDCR, ANALOG, PSI RANGE	NISO,ABS,NO FIT,RIBBON CBL
I				
	TE Part #FX1900-0000-0010-L			
	FX1900-10LB-SENSOR			
	Documents			
	CAD Files			
	3D PDF			
	3D			

Customer View Model

ENG\_CVM\_CVM\_86-300G-R\_G1.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_86-300G-R\_G1.3d\_igs.zip

86-300G-R

300 PSIG RIBBON CABLE MV PRESSURE SENSOR



English

Customer View Model ENG\_CVM\_CVM\_86-300G-R\_G1.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

86C

English