

### AMP | Junior Timer


TE Internal #: 962191-1

Housing for Female Terminals, Wire-to-Wire, 8 Position, .236 in [6 mm] Centerline, Brown, Wire & Cable, Power, Junior Timer

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > Timer Connector Housing



Connector System: Wire-to-Wire

Number of Positions: 8

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 6 mm [.236 in]

Sealable: No

All Timer Connector Housing (585)

# **Features**

### **Product Type Features**

Product Type Features	
Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	8
Number of Rows	2
Electrical Characteristics	
Nominal Voltage Architecture	12 V, 24 V
Body Features	

180°

Brown

Neutral

# **Contact Features**

Cable Exit Angle

Primary Product Color

Connector & Keying Code



Contact Size	2.8mm
Contact Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Contact Current Rating (Max)	30 A
Mechanical Attachment	
Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PA
Centerline (Pitch)	6 mm[.236 in]
Dimensions	
Connector Height	23 mm[.906 in]
Product Width	12.6 mm[.496 in]
Product Length	34.5 mm[1.358 in]
Row-to-Row Spacing	5 mm[.197 in]
Row-to-Row Spacing  Usage Conditions	5 mm[.197 in]
	5 mm[.197 in] 130 °C[266 °F]
Usage Conditions	
Usage Conditions  Operating Temperature (Max)	130 °C[266 °F]
Usage Conditions  Operating Temperature (Max)  Operating Temperature Range	130 °C[266 °F]
Usage Conditions  Operating Temperature (Max)  Operating Temperature Range  Operation/Application	130 °C[266 °F] -40 – 130 °C[-40 – 266 °F]
Usage Conditions  Operating Temperature (Max)  Operating Temperature Range  Operation/Application  Circuit Application	130 °C[266 °F] -40 – 130 °C[-40 – 266 °F]
Usage Conditions  Operating Temperature (Max)  Operating Temperature Range  Operation/Application  Circuit Application  Industry Standards	130 °C[266 °F] -40 – 130 °C[-40 – 266 °F]  Power
Usage Conditions  Operating Temperature (Max) Operating Temperature Range  Operation/Application  Circuit Application  Industry Standards  UL Flammability Rating	130 °C[266 °F] -40 – 130 °C[-40 – 266 °F]  Power
Usage Conditions  Operating Temperature (Max) Operating Temperature Range  Operation/Application  Circuit Application  Industry Standards  UL Flammability Rating  Packaging Features	130 °C[266 °F] -40 – 130 °C[-40 – 266 °F]  Power  UL 94HB
Usage Conditions  Operating Temperature (Max)  Operating Temperature Range  Operation/Application  Circuit Application  Industry Standards  UL Flammability Rating  Packaging Features  Packaging Method	130 °C[266 °F] -40 – 130 °C[-40 – 266 °F]  Power  UL 94HB

# **Product Compliance**



#### For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





Also in the Series | Junior Timer






Automotive Housings(77)



Automotive Terminals(16)



PCB Headers & Receptacles(3)

# Customers Also Bought



TE Part #284159-1 12 POS. 070 RCPT.HSG. & SEC.LO



TE Part #2302491-2 SOC CONN CVRASSY,2POS, AMPSEAL16,90DEG,MC



TE Part #1-1418437-1
6POS,AMP MCP2.8,REC HSG,ASSY,
SEALED



TE Part #1718049-1 6 POS.JPT HSG



TE Part #282224-1
ECONOSEAL RCPT CONT 0,5MM











# **Documents**

# Product Drawings 8P JUNIOR-TIMER HSG

German

#### **CAD Files**

Customer View Model ENG\_CVM\_962191-1\_B3.3d\_igs.zip

English

**Customer View Model** 

Housing for Female Terminals, Wire-to-Wire, 8 Position, .236 in [6 mm] Centerline, Brown, Wire & Cable, Power, Junior Timer



ENG\_CVM\_962191-1\_B3.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_962191-1\_B3.2d\_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# Datasheets & Catalog Pages

Timer Interconnection System

English