FASTON | FASTON 375

TE Internal #: 962834-1

Quick Disconnects, Receptacle, 13-11 AWG Wire Size, 2.62-4.17 mm² Wire Size, Mating Tab Width 9.53 mm [.375 in], Straight,


FASTON 375

View on TE.com >




Terminals & Splices > Quick Disconnects











Quick Disconnect Terminal Type: Receptacle

Wire Size: 2.62 – 4.17 mm²

Mating Tab Width: 9.53 mm [.375 in]

Mating Tab Thickness: 1.2 mm [.047 in]

Features

Product Type Features

Insertion Force	Normal
Configuration Features	
Compatible With Wire & Cable Type	Discrete Wire
Contact Features	
Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	9.53 mm[.375 in]
Mating Tab Thickness	1.2 mm[.047 in]
Terminal Orientation	Straight
Contact Base Material	Phosphor Bronze
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open
Termination Features	

Wire & Cable

Product Terminates To



Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple
Dimensions	
Terminal Material Thickness	.51 mm[.02 in]
Product Length	27 mm[1.063 in]
Compatible Insulation Diameter Range	3.3 – 4.5 mm[.13 – .177 in]
Wire Size	2.62 – 4.17 mm ²
Usage Conditions	
Insulation Option	Uninsulated
Industry Standards	
Agency/Standard	UL
Packaging Features	

1600

Reel

Product Compliance

Packaging Quantity

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts










Also in the Series | FASTON 375







Customers Also Bought





















Documents

Product Drawings

FF 374 REC 2.5-4 MM2 PLAIN CUSN4

English

CAD Files

Customer View Model

ENG_CVM_962834-1_F.3d_igs.zip

English

Customer View Model

ENG_CVM_962834-1_F.3d_stp.zip

English

Customer View Model

ENG_CVM_962834-1_F.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

1654742_HOUSEHOLD_APPLIANCES_RAST5

English

Product Specifications

Application Specification

English