




Micro Timer III, Timer Connector System

TE Internal #: 963900-2

Automotive Terminals, Tab, Mating Tab Width 1.6 mm [.063 in], Tab Thickness .6 mm [.024 in], 20 – 17 AWG Wire Size, Timer Connector System

[View on TE.com >](#)

Terminals & Splices > Automotive Terminals > TIMER, RECEPTACLE AND TAB



Terminal Type: **Tab**

Mating Tab Width: **1.6 mm [.063 in]**

Mating Tab Thickness: **.6 mm [.024 in]**

Terminal Transmits: **0 – 24 A (Low Power)**

Wire Size: **20 – 17 AWG**

[All TIMER, RECEPTACLE AND TAB \(348\)](#)

Features

Product Type Features

Receptacle Style	180°
Sealable	No
Primary Locking Feature	Locking Lance

Contact Features

Contact Size	1.6mm
Contact Fabrication	Stamped & Formed
Wire Contact Termination Area Plating Material	Tin
Typical Current Rating	10 A
Crimp Type	F-Crimp
Terminal Type	Tab
Mating Tab Width	1.6 mm[.063 in]
Mating Tab Thickness	.6 mm[.024 in]
Interface Plating	Tin (Sn)



Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire

Dimensions

Compatible Insulation Diameter Range	1.4 – 2.1 mm [.055 – .083 in]
Wire Size	.5 – 1 mm ²
Wire Size Search	17 AWG, 18 AWG, 19 AWG, 20 AWG

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature (Max)	80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C, 130 °C [176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F][266 °F]
Operating Temperature Range	-40 – 130 °C [-40 – 266 °F]

Operation/Application

Compatible With Wire Base Material	Copper
------------------------------------	--------

Industry Standards

Agency/Standard	DIN 72 551 Part 5 and 6
-----------------	-------------------------

Packaging Features

Packaging Quantity	6000
Packaging Method	Reel

Other

Terminal Transmits	0 – 24 A (Low Power)
--------------------	----------------------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)













EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer




This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts









 <p>TE Part # CAT-AM705-CH8173 AMP MCP Unsealed Connector Housings</p>	 <p>TE Part # 539960-1 AUSZ-WKZ,MICRO TIM.</p>	 <p>TE Part # 493224-1 HSG. 2P MICROTIMER TAB</p>	 <p>TE Part # 2151279-1 OCEAN_2.0_APPLICATOR-S-080F100O</p>
 <p>TE Part # 2151279-2 OCEAN_2.0_APPLICATOR-S-080F100O</p>	 <p>TE Part # 5-2151279-1 OCEAN_2.0_APPLICATOR-S-080F100O</p>	 <p>TE Part # 5-2151279-2 OCEAN_2.0_APPLICATOR-S-080F100O</p>	 <p>TE Part # 7-2151279-1 OCEAN_2.0_APPLICATOR-S-080F100O</p>
 <p>TE Part # 7-2151279-2 OCEAN_2.0_APPLICATOR-S-080F100O</p>	 <p>TE Part # 7-2151279-7 OCEAN_2.0_SPARE_PART_KIT-080F100O</p>	 <p>TE Part # 2-2151279-1 OCEAN_2.0_APPLICATOR-S-080F100O</p>	 <p>TE Part # 2385319-1 EXTRACTION TOOL</p>




Also in the Series | **Micro Timer III**



Also in the Series | **Timer Connector System**







PCB Headers & Receptacles(82)



Quick Disconnects(4)

Customers Also Bought

TE Part #1-967640-1
4POS MQS REC COD ATE Part #2-1355200-2
MCP2,8REC HSG ASY2PTE Part #2286003-3
2POS. DT. REC HSG. ASSY. SEALEDTE Part #1-1564526-1
18POS,TAB 1.6X0.6,TAB HSG,ASSYTE Part #1438153-5
1X6 SEALED MARKET KEY BTE Part #936777-2
MT-II/JPT SLD 20P PLUG ASSYTE Part #963900-1
TIMER, RECEPTACLE AND TABTE Part #1544603-1
1W 8MM NG1 SEALED CLIP ASSY
BLACK

Documents

Product Drawings

[TAB A 1.6x0.6 CONTACT CF SRC Sn](#)

English

[TAB A 1.6x0.6 CONTACT CF SRC Sn](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_963900-2_D.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_963900-2_D.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_963900-2_D.3d_stp.zip](#)



English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Timer Interconnection System

English

Product Specifications

Application Specification

German

Application Specification

English

Application Specification

English