AKUA020NN00090200000 - ACTIVE

TE Internal #: AKA020N00090200000 Standard Circular Connectors, Cable-to-Cable, 12 Position, Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PBT GF

View on TE.com >

Connectors > Circular Connectors > Standard Circular Connectors



Connector System: Cable-to-Cable

Number of Positions: 12

Sealable: No

Circuit Application: Signal

Connector Mounting Type: Cable Mount (Free-Hanging)

Features

Product Type Features



Product Type	Connector Assembly
Connector System	Cable-to-Cable
Sealable	No
Shell Type	Metal
Configuration Features	
Number of Positions	12
Number of Signal Positions	12
Electrical Characteristics	
Operating Voltage	160 VAC
Body Features	
Environmental Protection	IP67
Shell Plating Material	Electrodeposited Nickel
Shell Base Material	Zinc Alloy

AKUA020NN00090200000

Standard Circular Connectors, Cable-to-Cable, 12 Position, Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PBT GF



Mechanical Attachment

Mating Retention Type	Screw
Panel Mount Feature Type	Screw Mount
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Circular Connector Shell Size	23
Alignment Keyed	Uncoded
Dimensions	
Cable Diameter Range	3.5 – 5.6 mm[.14 – .22 in]
Usage Conditions	
Operating Temperature Range	-20 – 130 °C[-4 – 266 °F]
	-20 – 130 °C[-4 – 266 °F]
Operating Temperature Range	-20 – 130 °C[-4 – 266 °F] 500 Cycles
Operating Temperature Range Operation/Application	
Operating Temperature Range Operation/Application Durability Rating	500 Cycles
Operating Temperature Range Operation/Application Durability Rating Circuit Application	500 Cycles Signal

UL

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU

EU ELV Directive 2000/53/EC

China RoHS 2 Directive MIIT Order No 32, 2016

EU REACH Regulation (EC) No. 1907/2006

Halogen Content

Solder Process Capability

Compliant with Exemptions

Compliant with Exemptions

Restricted Materials Above Threshold

Current ECHA Candidate List: JUNE 2023 (235)

Candidate List Declared Against: JUNE 2022 (224)

SVHC > Threshold:

Pb (3.5% in Component)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Not Yet Reviewed for halogen content

Not reviewed for solder process capability

AKUA020NN00090200000

Standard Circular Connectors, Cable-to-Cable, 12 Position, Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PBT GF




Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought



AKUA020NN00090200000

Standard Circular Connectors, Cable-to-Cable, 12 Position, Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PBT GF





Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_AKA020N00090200000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_AKA020N00090200000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_AKA020N00090200000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use

Datasheets & Catalog Pages

fuer Datenblaetter, die online konfigurierbar sind

German

AKA020N00090200000

English

Product Specifications

German