# ANT-418-CW-RH-SMA V ACTIVE

TE Internal #: ANT-418-CW-RH-SMA
Whip Antenna, Single Band, Cat-M/NB-IoT / Cellular, External

Mount, Connector, SMA, Omnidirectional, Single Port, Gain < 0 dBi

View on TE.com >



#### Antennas



Wireless Application: Cat-M/NB-IoT, Cellular

Mounting Location: External
Mounting Type: Connector
Antenna Termination: SMA

Antenna Type: Whip

#### **Features**

### Product Type Features

Antenna Termination

Configuration Features			
Antenna Style	Whip		
Mounting Location	External		
Antenna Type	Whip		
Band Type	Single Band		
Port Configuration	Single Port		
Electrical Characteristics			
VSWR (Max)	<1.9:1		
Impedance	50 Ω		
Signal Characteristics			
Frequency Band	418 MHz		
Nominal Frequency Range	410 – 470		
Peak Gain	< 0 dBi		
Body Features			

SMA

6.32 g[.22292 oz]

Linear

Product Weight

Polarization

Mechanical Attachment



Mounting Type	Connector		
Dimensions			
Product Width	8.5 mm[.33 in]		

0 mm[0 in]

Product Length 51 mm[2.01 in]

Operation/Application

Product Height

Outdoor Antenna Environment

Directionality Omnidirectional

**Industry Standards** 

Wireless Application Cat-M/NB-IoT, Cellular Primary Application Cat-M/NB-IoT, Cellular

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)  Candidate List Declared Against: JUNE 2023 (235)  SVHC > Threshold:  Pb (4% in Component Part)  Article Safe Usage Statements:  Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished



product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

## Compatible Parts





SMA Jack 50 Ohm PCB Through Hole





## Customers Also Bought





TE Part #1-440055-2

2.0MM,HDR,12POS,R/A











TE Part #5406721-3

MJ,RJ45,SMT,BLACK,22"REEL



TE Part #1658621-9
40 NOVO MIL/CTR 15DP,LEAD FREE







#### **Documents**

**Product Drawings** 

Antenna 1/4 Wave Short 418MHz SMA

Whip Antenna, Single Band, Cat-M/NB-IoT / Cellular, External Mount, Connector, SMA, Omnidirectional, Single Port, Gain < 0 dBi



English

Datasheets & Catalog Pages

ANT-418-CW-RH

English