ANT-868-WRT-RPS V ACTIVE

TE Internal #: ANT-868-WRT-RPS

Dome/Puck Antenna, Single Band, LoRaWAN / LPWAN, External

Mount, Panel, RP-SMA, Omnidirectional, Single Port, Gain 3 < 6 dBi





Antennas



Wireless Application: LoRaWAN, LPWAN, Wi-Fi

Mounting Location: External

Mounting Type: Panel

Antenna Termination: RP-SMA
Antenna Type: Dome/Puck

Features

Product Type Features

Antenna Te	ermination	RP-SMA

Configuration Features

Antenna Style	Dome
Mounting Location	External
Antenna Type	Dome/Puck
Band Type	Single Band
Port Configuration	Single Port

Electrical Characteristics

VSWR (Max)	<1.9:1
Impedance	50 Ω

Signal Characteristics

Gain (Max)	1.5 dB
Frequency Band	868 MHz
Nominal Frequency Range	862 – 870
Peak Gain	3 < 6 dBi

Body Features

Product Weight	11.97 g[.42222 oz]

Mechanical Attachment



Polarization	Linear	
Mounting Type	Panel	
Dimensions		
Cable Length	.21 m[.71 ft]	
Product Width	19 mm[.75 in]	
Product Length	10 mm[.39 in]	
Product Height	0 mm[0 in]	
Operation/Application		
Antenna Environment	Outdoor	
Directionality	Omnidirectional	
Industry Standards		
Wireless Application	LoRaWAN, LPWAN, Wi-Fi	
Primary Application	LoRaWAN, LPWAN	

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.



Compatible Parts





TE Part # CONREVSMA002-SMD-G RP-SMA RA Jack 50 Ohm PCB Surface Mount





Customers Also Bought






















Documents

Product Drawings

Antenna Dome 868MHz RG174 216 RPS

English

Datasheets & Catalog Pages

868 MHz External Panel-Mount Antenna

Dome/Puck Antenna, Single Band, LoRaWAN / LPWAN, External Mount, Panel, RP-SMA, Omnidirectional, Single Port, Gain 3 < 6 dBi



English