

TE Internal #: ANT-916-CW-RCL Whip Antenna, Single Band, LoRaWAN / LPWAN, External Mount, Connector, RP-SMA, Omnidirectional, Single Port, Gain 3 < 6 dBi View on TE.com >



Antennas



Wireless Application: LoRaWAN, LPWAN, Wi-Fi

Mounting Location: External

Mounting Type: Connector

Antenna Termination: **RP-SMA**

Antenna Type: Whip

Features

Product Type Features

Antenna TerminationRP-SMAConfiguration FeaturesWhip

Mounting Location

External

Mounting Location	External
Antenna Type	Whip
Band Type	Single Band
Port Configuration	Single Port
Electrical Characteristics	
VSWR (Max)	<1.9:1
Impedance	50 Ω
Signal Characteristics	
Frequency Band	915 MHz
Nominal Frequency Range	902 – 930
Peak Gain	3 < 6 dBi
Body Features	
Product Weight	12.4 g[.43738 oz]
Mechanical Attachment	
Polarization	Linear

ANT-916-CW-RCL

Whip Antenna, Single Band, LoRaWAN / LPWAN, External Mount, Connector, RP-SMA, Omnidirectional, Single Port, Gain 3 < 6 dBi



Mounting Type	Connector
Dimensions	
Product Width	16.6 mm[.65 in]
Product Length	96 mm[3.78 in]
Product Height	0 mm[0 in]
Operation/Application	
Antenna Environment	Outdoor
Directionality	Omnidirectional
Industry Standards	
Wireless Application	LoRaWAN, LPWAN, Wi-Fi
Primary Application	LoRaWAN, LPWAN
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed

China RoHS 2 Directive MIIT Order No 32, 2016

Restricted Materials Above Threshold

EU REACH Regulation (EC) No. 1907/2006

Halogen Content

Solder Process Capability

Current ECHA Candidate List: JUNE 2023 (235) Not Yet Reviewed

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

ANT-916-CW-RCL

Whip Antenna, Single Band, LoRaWAN / LPWAN, External Mount, Connector, RP-SMA, Omnidirectional, Single Port, Gain 3 < 6 dBi



Compatible Parts



TE Part # CONREVSMA001-G RP-SMA Jack 50 Ohm PCB Through Hole



TE Part # CONREVSMA002-SMD-G RP-SMA RA Jack 50 Ohm PCB Surface Mount



TE Part # L9000251-01 RP-SMA Jack 50 Ohm .062 PCB Edge Mount



TE Part # L9000254-01 RP-SMA Jack 50 Ohm .031 PCB Edge Mount



Customers Also Bought







ANT-916-CW-RCL

Whip Antenna, Single Band, LoRaWAN / LPWAN, External Mount, Connector, RP-SMA, Omnidirectional, Single Port, Gain 3 < 6 dBi



Documents

Datasheets & Catalog Pages CW-RCL Series 916 MHz Right-Angle Whip Antenna English