# ANT-B5-PW-QW-UFL VACTIVE

TE Internal #: ANT-B5-PW-QW-UFL

Whip Antenna, Single Band, LTE / 5G / Cellular, External Mount, Panel, MHF / UMCC / U.FL, Omnidirectional, Single Port, Gain 0 <

3 dBi

View on TE.com >



#### Antennas



Wireless Application: 5G, Cat-M/NB-IoT, Cellular, LTE

Mounting Location: External

Mounting Type: Panel

Antenna Termination: MHF, MHF1, U.FL, UMCC

Antenna Type: Whip

### **Features**

### **Product Type Features**

Antenna Termination	MHF, MHF1, U.FL, UMCC
Configuration Features	
Antenna Style	Whip
Mounting Location	External
Antenna Type	Whip
Band Type	Single Band
Port Configuration	Single Port
Electrical Characteristics	
VSWR (Max)	<2.1:1
Impedance	50 Ω
Signal Characteristics	

Gain (Max)	1.2 dB
Frequency Band	824 – 894 MHz, 824 – 894 MHz
Nominal Frequency Range	824 – 1990
Peak Gain	0 < 3 dBi

#### Mechanical Attachment

Polarization	Linear
Mounting Type	Panel



#### **Dimensions**

Cable Length	.21 m[.71 ft]
Product Width	14.5 mm[.57 in]
Product Length	83.5 mm[3.29 in]
Product Height	0 mm[0 in]

#### Operation/Application

Operation/Application	
Antenna Environment	Outdoor
Directionality	Omnidirectional
Industry Standards	
Wireless Application	5G, Cat-M/NB-IoT, Cellular, LTE

5G, Cellular, LTE

### **Product Compliance**

**Primary Application** 

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.



## Compatible Parts





U.FL/MHF1 Jack 50 Ohm PCB Surface

Mount







## Customers Also Bought





TE Part #1-188275-4 Female-on-Board Connector, Top Entry



Antenna Short 915 SMA Jack











### **Documents**

**Product Drawings** 

Antenna 1/4 Wave Whip LTE B5 1.32 UFL

English

Datasheets & Catalog Pages Single-Band Monopole Antenna

English

### ANT-B5-PW-QW-UFL

Whip Antenna, Single Band, LTE / 5G / Cellular, External Mount, Panel, MHF / UMCC / U.FL, Omnidirectional, Single Port, Gain  $0 < 3 \ dBi$ 

