ANT-DB1-HDP-TNC - ACTIVE

TE Internal #: ANT-DB1-HDP-TNC Module Antenna, Multi Band, LTE / Cellular / 5G, External Mount, Adhesive, TNC / RP-TNC, Omnidirectional, Single Port, Gain 0 < 3 dBi

View on TE.com >



Antennas



Wireless Application: 5G, Cat-M/NB-IoT, Cellular, LTE

Mounting Location: External Mounting Type: Adhesive

Antenna Termination: RP-TNC, TNC

Antenna Type: Module

Features

Product Type Features

Antenna Termination RP-TNC, TNC Configuration Features Whip Antenna Style Whip Mounting Location External Antenna Type Module Band Type Multi Band Port Configuration Single Port Electrical Characteristics VSWR (Max) <1.5:1 Impedance 50 Ω Signal Characteristics Frequency Band 824 – 960 MHz Nominal Frequency Range 698 – 2700 Peak Gain 0 < 3 dBi Mechanical Attachment		
Antenna StyleWhipMounting LocationExternalAntenna TypeModuleBand TypeMulti BandPort ConfigurationSingle PortElectrical CharacteristicsVSWR (Max)<1.5:1	Antenna Termination	RP-TNC, TNC
Mounting LocationExternalAntenna TypeModuleBand TypeMulti BandPort ConfigurationSingle PortElectrical CharacteristicsVSWR (Max)VSWR (Max)<1.5:1	Configuration Features	
Antenna TypeModuleBand TypeMulti BandPort ConfigurationSingle PortElectrical CharacteristicsVSWR (Max)<1.5:1	Antenna Style	Whip
Band TypeMulti BandPort ConfigurationSingle PortElectrical CharacteristicsVSWR (Max)<1.5:1	Mounting Location	External
Port ConfigurationSingle PortElectrical Characteristics< 1.5:1VSWR (Max)<1.5:1Impedance50 ΩSignal Characteristics824 – 960 MHzFrequency Band824 – 960 MHzNominal Frequency Range698 – 2700Peak Gain0 < 3 dBi	Antenna Type	Module
Electrical Characteristics VSWR (Max) <1.5:1 Impedance 50Ω Signal Characteristics Frequency Band $824 - 960 \text{ MHz}$ Nominal Frequency Range $698 - 2700$ Peak Gain $0 < 3 \text{ dBi}$	Band Type	Multi Band
VSWR (Max)<1.5:1Impedance $50 Ω$ Signal Characteristics $824 - 960 \text{ MHz}$ Frequency Band $824 - 960 \text{ MHz}$ Nominal Frequency Range $698 - 2700$ Peak Gain $0 < 3 \text{ dBi}$	Port Configuration	Single Port
Impedance50 ΩSignal CharacteristicsFrequency Band824 – 960 MHzNominal Frequency Range698 – 2700Peak Gain0 < 3 dBi	Electrical Characteristics	
Signal CharacteristicsFrequency Band824 – 960 MHzNominal Frequency Range698 – 2700Peak Gain0 < 3 dBi	VSWR (Max)	<1.5:1
Frequency Band 824 – 960 MHz Nominal Frequency Range 698 – 2700 Peak Gain 0 < 3 dBi	Impedance	50 Ω
Nominal Frequency Range 698 – 2700 Peak Gain 0 < 3 dBi	Signal Characteristics	
Peak Gain 0 < 3 dBi	Frequency Band	824 – 960 MHz
	Nominal Frequency Range	698 – 2700
Mechanical Attachment	Peak Gain	0 < 3 dBi
	Mechanical Attachment	

Linear

Adhesive

Polarization

Mounting Type



Dimensions

Cable Length	3 m[9.84 ft]
Product Width	20 mm[.79 in]
Product Length	132.3 mm[5.21 in]
Product Height	12.4 mm[.49 in]

Operation/Application

Operation/Application	
Directionality	Omnidirectional
Industry Standards	
Wireless Application	5G, Cat-M/NB-IoT, Cellular, LTE

5G, Cellular, LTE

Product Compliance

Primary Application

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts







Documents

Datasheets & Catalog Pages
ANT-DB1-HDP-xxx

English