# 

TE Internal #: ANT-LTE-RPC-UFL PCB Antenna, Wide Band, Cellular / LTE, Internal/Embedded Mount, Adhesive, Solder, Omnidirectional, Single Port, Gain > 6 dBi View on TE.com >



Antennas



Wireless Application: Cat-M/NB-IoT, Cellular, LTE

Mounting Location: Internal/Embedded

Mounting Type: Adhesive

Antenna Termination: Solder

Antenna Type: PCB

### Features

### Product Type Features

Antenna Termination

Solder

## **Configuration Features**

Antenna Style

Mounting Location

Patch

Internal/Embedded

Mounting Location	Internal/Embedded
Antenna Type	PCB
Band Type	Wide Band
Port Configuration	Single Port
Electrical Characteristics	
VSWR (Max)	<2.5:1
Impedance	50 Ω
Signal Characteristics	
Gain (Max)	3.6 dB
Frequency Band	617 – 698 MHz
Nominal Frequency Range	617 – 4200
Peak Gain	> 6 dBi
Body Features	
Product Weight	3.2 g[.11287 oz]
Mechanical Attachment	

## ANT-LTE-RPC-UFL

PCB Antenna, Wide Band, Cellular / LTE, Internal/Embedded Mount, Adhesive, Solder, Omnidirectional, Single Port, Gain > 6 dBi



Polarization	Linear
Mounting Type	Adhesive
Dimensions	
Cable Length	.1 m[.33 ft]
Product Width	14.9 mm[.59 in]
Product Length	98.4 mm[3.87 in]
Product Height	.8 mm[.03 in]
Operation/Application	
Directionality	Omnidirectional
Industry Standards	
Wireless Application	Cat-M/NB-IoT, Cellular, LTE
Primary Application	Cellular, LTE
Product Compliance	
For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions

EU ELV Directive 2000/53/EC

Compliant with Exemptions

Not Yet Reviewed

China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

## ANT-LTE-RPC-UFL


PCB Antenna, Wide Band, Cellular / LTE, Internal/Embedded Mount, Adhesive, Solder, Omnidirectional, Single Port, Gain > 6 dBi



## Compatible Parts



Antenna Adh PCB RPC LTE 1.13 100



TE Part # CONMHF1-SMD-G-T U.FL/MHF1 Jack 50 Ohm PCB Surface Mount



TE Part # CONMHF1-SMD-T U.FL/MHF1 Jack 50 Ohm PCB Surface Mount



TE Part # CONUFL001-SMD Conn UFL MHF Straight PCB Mount Jack



## Customers Also Bought



Poke-In Connector, BUCHANAN WireMate

110 FASTON TAB TPBR

Antenna Whip 433MHz Swivel SMA





TE Part #2-1977223-4 FSM8JSMASTR=6MM TACT SWITCH, SMT 160gf,

## Documents

Datasheets & Catalog Pages LTE/LPWA Embedded Dipole Antenna

English