ASTA021NN00410100000 - ACTIVE

TE Internal #: ASA021N00410100000 Standard Circular Connectors, Cable-to-Cable, 12 Position, Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PBT GF

View on TE.com >

Connectors > Circular Connectors > Standard Circular Connectors



Connector System: Cable-to-Cable

Number of Positions: 12

Sealable: No

Circuit Application: Signal

Connector Mounting Type: Cable Mount (Free-Hanging)

Features

Product Type Features

connectivity

Product Type	Connector Assembly
Connector System	Cable-to-Cable
Sealable	No
Circular Connector Type	Plug
Shell Type	Metal
Configuration Features	
Number of Positions	12
Number of Signal Positions	12
Electrical Characteristics	
Operating Voltage	160 VAC
Body Features	
Environmental Protection	IP67
Shell Plating Material	Electrodeposited Nickel
Shell Base Material	Zinc Alloy

ASTA021NN00410100000

Standard Circular Connectors, Cable-to-Cable, 12 Position, Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PBT GF



Circular Connector Insulation Material Type	PBT GF
Mechanical Attachment	
Mating Retention Type	Speedtec (Triple Start Threaded)
Panel Mount Feature Type	Twist & Lock Flange
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Circular Connector Shell Size	23
Alignment Keyed	Uncoded
Dimensions	
Cable Diameter Range	6 – 10 mm[.23 – .39 in]
Usage Conditions	
Operating Temperature Range	-20 – 130 °C[-4 – 266 °F]
Operation/Application	
Durability Rating	500 Cycles
Circuit Application	Signal
Shielded	Yes

Industry Standards

UL Flammability Rating	UL 94V-0
Approved Standards	UL
Product Compliance	
For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023
	(235) Candidate List Declared Against: JUNE
	2022 (224)
	SVHC > Threshold:
	Pb (3.5% in COMPONENT PART)
	Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

C For support call+1 800 522 6752

ASTA021NN00410100000

Standard Circular Connectors, Cable-to-Cable, 12 Position, Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PBT GF



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # C0-0235-000-000 DIGITAL CRIMPING TOOL, SMALL

Customers Also Bought



ASTA021NN00410100000

Standard Circular Connectors, Cable-to-Cable, 12 Position, Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PBT GF







Documents

Product Drawings 623 PLUG, SPEEDTEC

English

CAD Files 3D PDF

3D

Customer View Model ENG_CVM_CVM_ASA021N00410100000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_ASA021N00410100000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_ASA021N00410100000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages ASA021N00410100000

English

fuer Datenblaetter, die online konfigurierbar sind

German

Product Specifications

German