# ASTA046NN0086050A000 V ACTIVE



TE Internal #: ASA046N0086050A000

Standard Circular Connectors, Cable-to-Cable, 12 Position, Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy,

PBT GF

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Cable-to-Cable

Number of Positions: 12

Sealable: No

Circuit Application: Signal

Connector Mounting Type: Cable Mount (Free-Hanging)

### **Features**

## Product Type Features

| Product Type            | Connector Assembly |
|-------------------------|--------------------|
| Connector System        | Cable-to-Cable     |
| Sealable                | No                 |
| Circular Connector Type | Plug               |
| Shell Type              | Metal              |
| Configuration Features  |                    |

| Number of Positions        | 12 |
|----------------------------|----|
| Number of Signal Positions | 12 |

#### **Electrical Characteristics**

| Operating Voltage | 32 VAC |
|-------------------|--------|
|-------------------|--------|

## **Body Features**

| Environmental Protection | IP67                    |
|--------------------------|-------------------------|
| Shell Plating Material   | Electrodeposited Nickel |
| Shell Base Material      | Zinc Alloy              |



| Circular Connector Insulation Material Type PBT |
|---|
|---|

#### Mechanical Attachment

| Mating Retention Type    | Speedtec (Triple Start Threaded) |
|--------------------------|----------------------------------|
| Panel Mount Feature Type | Screw Mount                      |
| Connector Mounting Type  | Cable Mount (Free-Hanging)       |

## **Housing Features**

#### **Dimensions**

| Cable Diameter Range | 9.5 – 12 mm[.37 – .47 in]  |
|----------------------|----------------------------|
| Cable Dameter Kange  | 7.0 12 11111[.07 . 17 111] |

## **Usage Conditions**

| Operating Temperature Range | -20 - 130 °C[-4 - 266 °F] |
|-----------------------------|---------------------------|

## Operation/Application

| Durability Rating   | 500 Cycles |
|---------------------|------------|
| Circuit Application | Signal     |
| Shielded            | Yes        |

## **Industry Standards**

| UL Flammability Rating | UL 94V-0 |
|------------------------|----------|
| Approved Standards     | UL       |

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant with Exemptions  |
|---|--|
| EU ELV Directive 2000/53/EC                   | Compliant with Exemptions  |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023 (235)  Candidate List Declared Against: JUNE 2022 (224)  SVHC > Threshold:  Pb (3.5% in Component)  Article Safe Usage Statements:  Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content                               | Not Yet Reviewed for halogen content   |
| Solder Process Capability                     | Not reviewed for solder process capability   |



#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





# Customers Also Bought

















Standard Circular Connectors, Cable-to-Cable, 12 Position, Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PBT GF







#### **Documents**

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_ASA046N0086050A000\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_ASA046N0086050A000\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_ASA046N0086050A000\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

ASA046N0086050A000

English

fuer Datenblaetter, die online konfigurierbar sind

German

09/27/2023 06:35AM | Page 4