BKUA145NN00420100000 ACTIVE



TE Internal #: BKA145N00420100000 Standard Circular Connectors, Cable-to-Cable, Power & Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy,

PBT GF, Size 23 View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Cable-to-Cable

Sealable: No

Circuit Application: Power & Signal

Connector Mounting Type: Cable Mount (Free-Hanging)

Shell Plating Material: Electrodeposited Nickel

Features

Product Type Features

Product Type	Connector Assembly
Connector System	Cable-to-Cable
Sealable	No
Shell Type	Metal

Electrical Characteristics

Body Features

Environmental Protection	IP67
Shell Plating Material	Electrodeposited Nickel
Shell Base Material	Zinc Alloy
Circular Connector Insulation Material Type	PBT GF

Mechanical Attachment

Mating Retention Type	Speedtec (Triple Start Threaded)
Connector Mounting Type	Cable Mount (Free-Hanging)



Housing Features

Circular Connector Shell Size	23
Alignment Keyed	0°
Dimensions	
Cable Diameter Range	9.5 – 14.5 mm[.37 – .57 in]
Usage Conditions	
Operating Temperature Range	-20 – 130 °C[-4 – 266 °F]
Operation/Application	
Durability Rating	500 Cycles
Circuit Application	Power & Signal
Shielded	Yes
Industry Standards	
UL Flammability Rating	UL 94V-0

UL

Product Compliance

Approved Standards

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) SVHC > Threshold: Pb (3.5% in Component) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products

Standard Circular Connectors, Cable-to-Cable, Power & Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PBT GF, Size 23



will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts





TE Part # C0-0003-000-000 POSITIONING INSERT FOR 1 MM CONTACTS



TE Part # C0-0101-000-000 CRIMPING TOOL SMALL WITH **POSITIONER**

TE Part # C0-0201-000-000 **CRIMPING TOOL MID-SIZE**

TE Part # C0-0235-000-000 DIGITAL CRIMPING TOOL, SMALL TE Part # C0-0236-000-000 DIGITAL CRIMPING TOOL, MID SIZE

Customers Also Bought



CONTACT SOCKET 2 MM



CONTACT SOCKET 0.6 MM



CONTACT PIN 3.6 MM



623 RECEPTACLE ANGLED ROTATABLE









Standard Circular Connectors, Cable-to-Cable, Power & Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PBT GF, Size 23





TE Part #EGC001N00000605000 615 ITEC RECEPTACLE, ANGLED

Documents

Product Drawings

923 EXTENSION, SPEEDTEC

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_BKA145N00420100000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_BKA145N00420100000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_BKA145N00420100000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

BKA145N00420100000

English

fuer Datenblaetter, die online konfigurierbar sind

German

Product Specifications

German

09/27/2023 06:35AM | Page 4