# CKUA269NN00450051000 V ACTIVE



TE Internal #: CKA269N00450051000

Standard Circular Connectors, Cable-to-Cable, Power & Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy,

PBT GF, Size 40

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Cable-to-Cable

Sealable: No

Circuit Application: Power & Signal

Connector Mounting Type: Cable Mount (Free-Hanging)

Shell Plating Material: Electrodeposited Nickel

# **Features**

# Product Type Features

onnector Assembly
ble-to-Cable
etal
ık O

## **Electrical Characteristics**

# **Body Features**

Environmental Protection	IP67
Shell Plating Material	Electrodeposited Nickel
Shell Base Material	Zinc Alloy
Circular Connector Insulation Material Type	PBT GF

#### Mechanical Attachment

Mating Retention Type	Speedtec (Triple Start Threaded)
Connector Mounting Type	Cable Mount (Free-Hanging)



## **Housing Features**

Circular Connector Shell Size	40
Alignment Keyed	0°
Dimensions	
Cable Diameter Range	16.5 – 25 mm[.65 – .98 in]
Usage Conditions	
Operating Temperature Range	-20 – 130 °C[-4 – 266 °F]
Operation/Application	
Durability Rating	500 Cycles
Circuit Application	Power & Signal
Shielded	Yes
Industry Standards	
UL Flammability Rating	UL 94V-0

UL

# **Product Compliance**

Approved Standards

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)  Candidate List Declared Against: JUNE 2022 (224)  SVHC > Threshold:  Pb (3.5% in Component part)  Article Safe Usage Statements:  Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

## Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

# Compatible Parts



TE Part # CDA265N00000001000 940 BULKHEAD CONNECTOR



TE Part # CSA265N00450001000 940 PLUG



TE Part # C0-0008-000-000 CRIMPING TOOL LARGE



POSITIONING INSERT FOR 2 MM CONTACTS



TE Part # C0-0201-000-000 CRIMPING TOOL MID-SIZE

TE Part # C0-0236-000-000 DIGITAL CRIMPING TOOL, MID SIZE

TE Part # C0-0313-000-000 CRIMPING DEVICE HC20 IN CASE

# Customers Also Bought



TE Part #927777-1 JUNIOR POWER TIMER CONTACT



TE Part #61-0020-011-000 **CONTACT PIN 1 MM** 





940 BULKHEAD CONNECTOR





TE Part #HEC005N00000300000 723 HTEC RECEPTACLE, SPEEDTEC

TE Part #2-1393560-7 V42254A 152V 1=SUB D BOLZENSA



Standard Circular Connectors, Cable-to-Cable, Power & Signal, Cable Mount (Free-Hanging), Electrodeposited Nickel, Zinc Alloy, PBT GF, Size 40







# **Documents**

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_CKA269N00450051000\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_CKA269N00450051000\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_CKA269N00450051000\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# Datasheets & Catalog Pages

fuer Datenblaetter, die online konfigurierbar sind

German

CKA269N00450051000

English

**Product Specifications** 

German