CONREVSMA004 V ACTIVE

TE Internal #: CONREVSMA004 RP-SMA RF Interface, Jack, 50 Ω, Threaded, 12.4 GHz Operating Frequency, 1 Position, Printed Circuit Board, Panel Mount, -65 – 165 °C [-85 – 329 °F]

View on TE.com >



Connectors > RF Connectors > Coax Connectors



RF Interface: **RP-SMA**

RF Connector Style: Jack

Impedance: 50Ω

RF Connector Coupling Mechanism: Threaded

Operating Frequency: 12.4 GHz

Features

Product Type Features

Connector Product Type	Connector Assembly
RF Interface	RP-SMA
RF Connector Style	Jack

Sealable	No	
Connector & Contact Terminates To	Printed Circuit Board	
Configuration Features		
Number of Positions	1	
Number of Coaxial Contacts	1	
Electrical Characteristics		
Impedance	50 Ω	
Body Features		
Cable Connector Orientation	Straight	
Body Material	Brass	
Body Material Finish	Plated	
Body Plating Material	Nickel	
Contact Features		
RF Connector Center Contact Plating Material	Gold	
RF Connector Center Contact Material	Brass	

CONREVSMA004

RP-SMA RF Interface, Jack, 50 $\Omega,$ Threaded, 12.4 GHz Operating Frequency, 1 Position, Printed Circuit Board, Panel Mount, -65 – 165 °C [-85 – 329 °F]



Termination Features

Termination Method to Wire & Cable	Solder
Mechanical Attachment	
RF Connector Coupling Mechanism	Threaded
Connector Mounting Type	Panel Mount
RF Contact Captivation Method	Mechanical
Detent	Without
Usage Conditions	
Operating Temperature Range	-65 – 165 °C[-85 – 329 °F]
Operation/Application	
Operating Frequency	12.4 GHz
Circuit Application	Signal
Packaging Features	
Packaging Quantity	100
Packaging Method	Bulk
Other	
Lockwasher Material	Brass
Dielectric Material	PTFE
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Lockwasher Material	Brass
Dielectric Material	PTFE
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these

CONREVSMA004

RP-SMA RF Interface, Jack, 50 Ω, Threaded, 12.4 GHz Operating Frequency, 1 Position, Printed Circuit Board, Panel Mount, -65 – 165 °C [-85 – 329 °F]



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



TE Part # L9000259-01 RP-SMA Plug 50 Ohm .062 PCB Edge Mount

Customers Also Bought









TE	-ETE	= TE	TE
TE Part #5745434-8 09 PLUG RA/MS 454	TE Part #8-215083-4 MICRO-MATCH MOW.14P	TE Part #1838891-1 M12 Mtl FEMALE PNL CONN. Sldr Rear (Hex)	TE Part #1-188275-4 MICRO-MATCH SMD FTE
		TE TE	
TE Part #ANT-916-CW-RH-SMA Antenna 1/4 Wave Short 916MHz SMA	TE Part #CONMMCX001 MMCX Jack 50 Ohm PCB Through Hole	TE Part #CONMMCX001-SMD MMCX Jack 50 Ohm PCB Surface Mount	TE Part #CONMMCX001-SMD-T MMCX Jack 50 Ohm PCB Surface Mount

CONREVSMA004

RP-SMA RF Interface, Jack, 50 Ω, Threaded, 12.4 GHz Operating Frequency, 1 Position, Printed Circuit Board, Panel Mount, -65 – 165 °C [-85 – 329 °F]





Documents

Product Drawings RP-SMA Jack 50 Ohm Panel Mount

English

Datasheets & Catalog Pages RP-SMA FEMALE BULK HEAD FRONT MONT W/SOLDER POT

English