# CONSMA002 ~ ACTIVE

TE Internal #: CONSMA002 SMA RF Interface, Jack, 50 Ω, Threaded, 12.4 GHz Operating Frequency, 1 Position, Printed Circuit Board, Board Mount, -65 – 165 °C [-85 – 329 °F]

#### View on TE.com >



Connectors > RF Connectors > Coax Connectors



RF Interface: SMA RF Connector Style: Jack Impedance: 50 Ω RF Connector Coupling Mechanism: Threaded Operating Frequency: 12.4 GHz

### Features

#### **Product Type Features**

Connector Product Type	Connector Assembly
RF Interface	SMA
RF Connector Style	Jack

Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
PCB Mount Orientation	Right Angle
Number of Positions	1
Number of Coaxial Contacts	1
Electrical Characteristics	
Impedance	50 Ω
Body Features	
Cable Connector Orientation	Right Angle
Body Material	Brass
Body Material Finish	Plated
Body Plating Material	Nickel
Contact Features	
RF Connector Center Contact Plating Material	Gold
	00/00/00000

#### CONSMA002

SMA RF Interface, Jack, 50 Ω, Threaded, 12.4 GHz Operating Frequency, 1 Position, Printed Circuit Board, Board Mount, -65 – 165 °C [-85 – 329 °F]



RF Connector Center Contact Material	Beryllium Copper
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Solder
Termination Method to Wire & Cable	Solder
Mechanical Attachment	
RF Connector Coupling Mechanism	Threaded
Connector Mounting Type	Board Mount
RF Contact Captivation Method	Mechanical
Detent	Without
Usage Conditions	
Operating Temperature Range	-65 – 165 °C[-85 – 329 °F]
Operation/Application	
Operating Frequency	12.4 GHz
Circuit Application	Signal
Packaging Features	
Packaging Quantity	50
Packaging Method	Bulk



#### Other

Dielectric Material	PTFE			
Product Compliance For compliance documentation, visit the product page on TE.com>				
EU RoHS Directive 2011/65/EU	Compliant with Exemptions			
EU ELV Directive 2000/53/EC	Not Yet Reviewed			
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold			
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Not Yet Reviewed			
Halogen Content	Not Yet Reviewed for halogen content			
Solder Process Capability	Not reviewed for solder process capability			
Product Compliance Disclaimer	aproconte our ourrent actual knowledge			

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as

#### CONSMA002

SMA RF Interface, Jack, 50  $\Omega,$  Threaded, 12.4 GHz Operating Frequency, 1 Position, Printed Circuit Board, Board Mount, -65 – 165 °C [-85 – 329 °F]




EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

### **Compatible Parts**



## Customers Also Bought



### Documents

#### Product Drawings SMA RA Jack 50 Ohm PCB Through Hole

English

#### CONSMA002

SMA RF Interface, Jack, 50 Ω, Threaded, 12.4 GHz Operating Frequency, 1 Position, Printed Circuit Board, Board Mount, -65 – 165 °C [-85 – 329 °F]



Datasheets & Catalog Pages SMA FEMALE RIGHT ANGLE PCB MOUNT

English