# CONSMB012-G VACTIVE

TE Internal #: CONSMB012-G SMB RF Interface, Plug, 50  $\Omega$ , RG 316 / RG 174, Snap-On, 12 GHz Operating Frequency, 1 Position, Wire & Cable, Cable Mount (Free-Hanging)

#### View on TE.com >



Connectors > RF Connectors > Coax Connectors



RF Interface: SMB

RF Connector Style: Plug

Impedance:  $50 \Omega$ 

Compatible With RF Cable Type: RG 174, RG 316

RF Connector Coupling Mechanism: Snap-On

## Features

### Product Type Features

| Connector Product Type | Connector Assembly |
|------------------------|--------------------|
| RF Interface           | SMB                |
| RF Connector Style     | Plug               |

| Compatible With RF Cable Type     | RG 174, RG 316 |
|-----------------------------------|----------------|
| Sealable                          | No             |
| Connector & Contact Terminates To | Wire & Cable   |
| Configuration Features            |                |
| Number of Positions               | 1              |
| Number of Coaxial Contacts        | 1              |
| Electrical Characteristics        |                |
| Impedance                         | 50 Ω           |
| Body Features                     |                |
| Cable Connector Orientation       | Right Angle    |
| Body Material                     | Brass          |
| Body Material Finish              | Plated         |
| Body Plating Material             | Gold           |
| Contact Features                  |                |
| Ferrule Plating Material          | Gold           |

**C** For support call+1 800 522 6752

## CONSMB012-G

SMB RF Interface, Plug, 50 Ω, RG 316 / RG 174, Snap-On, 12 GHz Operating Frequency, 1 Position, Wire & Cable, Cable Mount (Free-Hanging)



| Ferrule Material                             | Brass                      |
|--|----------------------------|
| RF Connector Center Contact Plating Material | Gold                       |
| RF Connector Center Contact Material         | Beryllium Copper           |
| Termination Features                         |                            |
| Termination Method to Wire & Cable           | Crimp                      |
| Mechanical Attachment                        |                            |
| RF Connector Coupling Mechanism              | Snap-On                    |
| Connector Mounting Type                      | Cable Mount (Free-Hanging) |
| RF Contact Captivation Method                | Mechanical                 |
| Detent                                       | Without                    |
| Usage Conditions                             |                            |
| Operating Temperature Range                  | -65 – 165 °C[-85 – 329 °F] |
| Operation/Application                        |                            |
| Operating Frequency                          | 12 GHz                     |
| Circuit Application                          | Signal                     |
| Packaging Features                           |                            |
|  |                            |

# Packaging Quantity

Packaging Method

Bag

50

#### Other

|--|

#### PTFE

# Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant with Exemptions   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Not Yet Reviewed  |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold                                |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023<br>(235)<br>Not Yet Reviewed |
| Halogen Content                               | Not Yet Reviewed for halogen content                                |
| Solder Process Capability                     | Not reviewed for solder process capability                          |

Product Compliance Disclaimer

## CONSMB012-G

SMB RF Interface, Plug, 50 Ω, RG 316 / RG 174, Snap-On, 12 GHz Operating Frequency, 1 Position, Wire & Cable, Cable Mount (Free-Hanging)



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

# **Compatible Parts**



TE Part # CONSMB001-G SMB Jack 50 Ohm PCB Through Hole



TE Part # CONSMB001-SMD-G SMB Jack 50 Ohm PCB Surface Mount



TE Part # CONSMB002-G SMB Jack 50 Ohm PCB Through Hole



TE Part # L9000282-01 SMB Jack .062 PCB Edge Mount



# **Customers Also Bought**



## CONSMB012-G

SMB RF Interface, Plug, 50 Ω, RG 316 / RG 174, Snap-On, 12 GHz Operating Frequency, 1 Position, Wire & Cable, Cable Mount (Free-Hanging)



|   | MEAS<br>KW 722  |   |  |
|---|---|---|--|
| TE Part #CONSMB007-G<br>SMB Plug 50 Ohm Cable Crimp | TE Part #G-MRCO-001<br>KMY20M FIELD SENSOR W BIAS<br>MAGNET | TE Part #284884-E<br>STVB/2 16 F AB 0374 7-00 0606 2,5 *<br>247 | TE Part #384268-E<br>STVB/2 16 M AB 0374 4-00 0606 * 8360<br>247 |



## Documents

Datasheets & Catalog Pages SMB Plug Cable-Mount Connector English