# CSE-SBRM-152-SBRM

TE Internal #: CSE-SBRM-152-SBRM SMB Cable Assembly, .5 ft [.15 m], Red Cable, 4 GHz Operating Frequency, 50 Ω, FEP, 25 AWG, .098 in [2.49 mm] Diameter, SMB Plug, SMB Plug

### View on TE.com >



Cable Assemblies > RF Cable Assemblies



## Connector Type (End A): SMB Plug

Jacket Material: FEP

Cable Assembly Length: .15 m [.5 ft]

Cable Color: Red

Operating Temperature Range: -50 – 200 °C [-58 – 392 °F]

## Features

## Product Type Features

Coax Cable Type	RG-316
Connector Type (End A)	SMB Plug
Connector Type (End B)	SMB Plug

Cable Assembly Type	SMB							
Configuration Features								
Number of Connectorized Ends	2							
Electrical Characteristics								
Impedance	50 Ω							
Body Features								
Body Plating Material	Gold							
Jacket Material	FEP							
Cable Color	Red							
Contact Features								
Center Contact Plating	Gold							
Dimensions								
Wire Size	25 AWG							
Outside Cable Diameter	2.49 mm[.098 in]							

## CSE-SBRM-152-SBRM

SMB Cable Assembly, .5 ft [.15 m], Red Cable, 4 GHz Operating Frequency, 50  $\Omega$ , FEP, 25 AWG, .098 in [2.49 mm] Diameter, SMB Plug, SMB Plug



## **Usage Conditions Operating Temperature Range** -50 - 200 °C[-58 - 392 °F] **Operation/Application** Shielded Yes **Operating Frequency** 4 GHz Other **Dielectric Material** PTFE Cable Assembly Length .15 m[.5 ft] **Product Compliance** For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU Compliant with Exemptions EU ELV Directive 2000/53/EC Not Yet Reviewed China RoHS 2 Directive MIIT Order No 32, 2016 Restricted Materials Above Threshold EU REACH Regulation (EC) No. 1907/2006 Current ECHA Candidate List: JUNE 2023 (235) Not Yet Reviewed Halogen Content Not Yet Reviewed for halogen content

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

# **Compatible Parts**

## CSE-SBRM-152-SBRM

SMB Cable Assembly, .5 ft [.15 m], Red Cable, 4 GHz Operating Frequency, 50 Ω, FEP, 25 AWG, .098 in [2.49 mm] Diameter, SMB Plug, SMB Plug





TE Part # CONSMB001-1-G SMB Jack 50 Ohm PCB Through Hole



TE Part # CONSMB001-G SMB Jack 50 Ohm PCB Through Hole



TE Part # CONSMB001-SMD-G SMB Jack 50 Ohm PCB Surface Mount

# Customers Also Bought





## Documents

**Product Drawings** SMB to SMB 152mm RG316

English

Datasheets & Catalog Pages SMB Plug to SMB Plug Cable Assembly English