# CSJ-RGFB-100-MHF3 <

TE Internal #: CSJ-RGFB-100-MHF3 RP-SMA to MHF3 Cable Assembly, .33 ft [.1 – 1 m], Black Cable, 6 GHz Operating Frequency, 50 Ω, PFA, 34 AWG, .031 in [.81 mm] Diameter, RP SMA Plug

#### View on TE.com >



Cable Assemblies > RF Cable Assemblies



#### Connector Type (End A): **RP SMA Plug**

Jacket Material: **PFA** 

Cable Assembly Length: .1 – 1 m [.33 ft]

Cable Color: Black

Operating Temperature Range: -40 – 90 °C [-40 – 194 °F]

### Features

### **Product Type Features**

Coax Cable Type	.81 mm
Connector Type (End A)	RP SMA Plug
Connector Type (End B)	MHF1 Plug

Cable Assembly Type	RP-SMA to MHF3			
Configuration Features				
Number of Connectorized Ends	2			
Electrical Characteristics				
Impedance	50 Ω			
Body Features				
Body Plating Material	Gold			
Jacket Material	PFA			
Cable Color	Black			
Contact Features				
Center Contact Plating	Gold			
Dimensions				
Wire Size	34 AWG			
Outside Cable Diameter	.81 mm[.031 in]			

## CSJ-RGFB-100-MHF3

RP-SMA to MHF3 Cable Assembly, .33 ft [.1 – 1 m], Black Cable, 6 GHz Operating Frequency, 50  $\Omega$ , PFA, 34 AWG, .031 in [.81 mm] Diameter, RP SMA Plug



### Usage Conditions

Operating Temperature Range	-40 – 90 °C[-40 – 194 °F]				
Operation/Application					
Shielded	Yes				
Operating Frequency	6 GHz				
Other					
Dielectric Material	FEP				
Cable Assembly Length	.1 – 1 m[.33 ft]				
Product Compliance For compliance documentation, visit the product page on TE.com>					
EU RoHS Directive 2011/65/EU	Compliant with Exemptions				
EU ELV Directive 2000/53/EC	Not Yet Reviewed				
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold				
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)				

#### Halogen Content

Not Yet Reviewed for halogen content

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

## **Compatible Parts**

## CSJ-RGFB-100-MHF3

RP-SMA to MHF3 Cable Assembly, .33 ft [.1 – 1 m], Black Cable, 6 GHz Operating Frequency, 50  $\Omega$ , PFA, 34 AWG, .031 in [.81 mm] Diameter, RP SMA Plug





## Customers Also Bought



UIVIINSA SVV RLEVU.00IN 3A/ 1.3A AC	PLG, 9P, BLK, E, THD, 8/12/10, 5	ADAPTER, FOR TAB HOUSING, ASSY	Backsnells, DEUTSCH DTM
SC PCB			
30100			



## Documents

Product Drawings RP-SMA to MHF3 100mm 0.81 OD

English

Datasheets & Catalog Pages CBL ASSEMBLY, MHF3 TO FEM. BLKHD RP-SMA, 0.81mm CBL English