D369-P66-NS1 <

DEUTSCH | DEUTSCH 369

TE Internal #: D369-P66-NS1 Standard Rectangular Connectors, Connector Assembly, Plug, Mating Alignment, Keyed Mating Alignment Type, Mating Retention, Crimp, DEUTSCH 369

View on TE.com >



Connectors > Rectangular Connectors > Standard Rectangular Connectors > Rectangular Connectors: 6-Way Plug



Connector Product Type: Connector Assembly

Connector & Housing Type: Plug

Mating Alignment: With

Mating Alignment Type: Keyed

Mating Retention: With

All Rectangular Connectors: 6-Way Plug (26)

Features

Product Type Features

Connector Seal & Plug Type

Triple-Seal

Connector Shell Size	06
Connector Product Type	Connector Assembly
Connector & Housing Type	Plug
Connector System	Wire-to-Wire
Insertion Force Type	Normal
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Cavities	6
Contacts Preloaded	Yes
Number of Power Positions	6
Number of Columns	3
Number of Signal Positions	6
Number of Positions	6
Number of Rows	2

Standard Rectangular Connectors, Connector Assembly, Plug, Mating Alignment, Keyed Mating Alignment Type, Mating Retention, Crimp, DEUTSCH 369



Electrical Characteristics

Operating Voltage	400 VAC
Body Features	
Connector Seal Color	Natural
Seal Type	Grommet Seal, Interfacial Seal
Cable Exit Angle	180°
Seal Material	Fluorosilicone
Connector & Keying Code	Ν
Contact Features	
Contact Size	Size 22
Contact Type	Socket
Wire Contact Termination Area Plating Material	Gold
Contact Mating Area Plating Material	Gold
Contact Retention Within Housing	With
Contact Current Rating (Max)	5 A
Termination Features	
Termination Method to Wire & Cable	Crimp

Mechanical Attachment

Strain Relief	Without
Mating Alignment	With
Mating Alignment Type	Keyed
Mating Retention	With
Mating Retention Type	Button Latch
Housing Features	
Shell Material	Composite
Housing Material	Composite
Housing Color	Black
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Row-to-Row Spacing	2.54 mm[.1 in]
Compatible Insulation Diameter Range	.71 – 1.37 mm[.028 – .054 in]
Usage Conditions	

Standard Rectangular Connectors, Connector Assembly, Plug, Mating Alignment, Keyed Mating Alignment Type, Mating Retention, Crimp, DEUTSCH 369



Operating Temperature Range	-55 – 175 °C[-67 – 347 °F]
Operation/Application	
Shielded	No
Circuit Application	Power & Signal
Packaging Features	
Packaging Quantity	1
Packaging Method	Package
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233)
	SVHC > Threshold: Pb (1.2% in Contact)

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Not reviewed for solder process capability

Halogen Content

Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

Standard Rectangular Connectors, Connector Assembly, Plug, Mating Alignment, Keyed Mating Alignment Type, Mating Retention, Crimp, DEUTSCH 369





369 6 WAY REC, CRIMP, PIN

369 6 WAY PANEL MOUNT REC, CRIMP, PIN

Also in the Series DEUTSCH 369



Customers Also Bought



TE



TE Part #60419-2 250 FASTON FLAG REC 18-14 AWG TPBR

NATRUAL

TE Part #1-480306-1 250 FASTON INSULATION POD., REC.,

369 3 WAY BACKSHELL STRAIGHT

TE Part #D369-STB-6 369 6 WAY BACKSHELL STRAIGHT TIE WRAP



TE Part #D369-P99-NS1 369 9 WAY PLUG, CRIMP, SKT TE Part #12333-22

CONT SOC ASSY

TE Part #1617086-6 3SBM1071A2 = M39016/31-003M TE Part #CB1051-000 D-500-0463-J24-R120

Standard Rectangular Connectors, Connector Assembly, Plug, Mating Alignment, Keyed Mating Alignment Type, Mating Retention, Crimp, DEUTSCH 369



Documents

Product Drawings 369 6 WAY PLUG, CRIMP, SKT

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_D369-P66-NS1_3_c-d369-p66-ns1-3.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_D369-P66-NS1_3_c-d369-p66-ns1-3.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_D369-P66-NS1_3_c-d369-p66-ns1-3.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.