

MEAS | MEAS DP86 Series

TE Internal #: DP86-300D TE Internal Description: 300 PSID MV DIFFERENTIAL PRESSURE SENSOR Differential MV Output Pressure Sensor

View on TE.com >



Sensors > Pressure Sensors > Media Isolated Pressure Sensors > Differential MV Output Pressure Sensor



Pressure: [300 psi]

Media Isolated Pressure Sensor Type: Media Isolated mV Output Pressure Sensors

Media Isolated Pressure Sensor Style: Differential

Media Isolated Pressure Sensor Supply Voltage: 5 V

Operating Temperature Range: -40 – 125 °C [-40 – 257 °F]

All Differential MV Output Pressure Sensor (8)

Features

Product Type Features

Media Isolated Pressure Sensor Type

Media Isolated mV Output Pressure Sensors

Media Isolated Pressure Sensor Style	Differential							
Configuration Features								
Pressure Port/Fitting	O- Ring Mount							
Electrical Characteristics								
Supply Current	1.5 mA							
Media Isolated Pressure Sensor Supply Voltage	5 V							
Dimensions								
Dimensions	Dia 15.82 x 17.52 mm[Dia .622 x .69 in]							
Usage Conditions								
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]							
Operation/Application								
Proof Pressure Range	3X							
	300 psi							
Packaging Features								

C For support call+1 800 522 6752

300 PSID MV DIFFERENTIAL PRESSURE SENSOR



Media Isolated Pressure Sensor Package	O-Ring Mount							
Other								
Non-Linearity	± .1 %							
Product Compliance For compliance documentation, visit the product page on TE.com>								
EU RoHS Directive 2011/65/EU	Compliant							
EU ELV Directive 2000/53/EC	Compliant							
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold							
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC							
Halogen Content	Not Yet Reviewed for halogen content							
Solder Process Capability	Not reviewed for solder process capability							

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




Also in the Series | MEAS DP86 Series

C For support call+1 800 522 6752

300 PSID MV DIFFERENTIAL PRESSURE SENSOR





Customers Also Bought



FLEXIBLE CABLE BOOT, SIZE 11	CABLE GRIPPER, SIZE 11	30 PSIA WELDABLE PRESSURE	NISO,1/4NPT,7/8HEX,UNCOMP
		SENSOR	

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DP86-300D_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DP86-300D_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DP86-300D_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

DP86

English

& For support call+1 800 522 6752

DP86-300D

300 PSID MV DIFFERENTIAL PRESSURE SENSOR

