

## DEUTSCH | DEUTSCH DT, DEUTSCH DTM

TE Internal #: DTM04-08PB

Housing for Male Terminals, Wire-to-Wire, 8 Position, .165 in [4.19 mm] Centerline, Sealable, Black, Wire & Cable, Power & Signal,

Hybrid

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DTM Housings



Connector System: Wire-to-Wire

Number of Positions: 8

Connector & Housing Type: Housing for Male Terminals

Centerline (Pitch): 4.19 mm [ .165 in ]

Sealable: Yes

All DEUTSCH DTM Housings (109)

## **Features**

## **Product Type Features**

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Male Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing
Configuration Features	
Blank Cavity Position	0
Number of Positions	8
Number of Rows	2
Electrical Characteristics	
Operating Voltage	250 VAC
Nominal Voltage Architecture	12 V, 24 V, 48 V
Body Features	

180°

Cable Exit Angle



Primary Product Color	Black
Connector & Keying Code	В
Contact Features	
Contact Size	Size 20
Contact Type	Pin
Mating Pin Diameter	1.02 mm[.04 in]
Contact Current Rating (Max)	7.5 A
Mechanical Attachment	
Terminal Position Assurance	Yes
Strain Relief	Add By Accessory
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PA GF
Centerline (Pitch)	4.19 mm[.165 in]
Dimensions	
Connector Height	31.62 mm[1.245 in]
Product Width	20.22 mm[.796 in]
Product Length	43.69 mm[1.72 in]
Row-to-Row Spacing	7.11 mm[.28 in]
Compatible Insulation Diameter Range	1.35 – 3.05 mm[.053 – .12 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Degree of Protection	IP68, IP6K9K
Agency/Standard	SAE J2030
UL Flammability Rating	20mm Flame Test per Standard UL-94



Packaging Quantity	500
Packaging Method	Box
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)  Candidate List Declared Against: JUNE 2023 (235)  SVHC > Threshold:  Octamethylcyclotetrasiloxane (D4) (.5% in Component Part)  Dodecamethylcyclohexasiloxane (D6) (.5% in Component Part)  Decamethylcyclopentasiloxane (D5) (.5% in Component Part)  Article Safe Usage Statements:  Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts





TE Part # CAT-D48-SP729 **DEUTSCH Sealing Plugs** 



TE Part # CAT-D485-CH8172 DEUTSCH DTM Housings



TE Part # CAT-D487-M8649 DEUTSCH DT Mounting Clips



TE Part # CAT-D48-ST273 **DEUTSCH Solid Contacts** 



TE Part # 1060-20-0277 PIN, SF, SIZE 20, 16-22, SN/SN



TE Part # CAT-D485-W416 DEUTSCH DTM Wedgelocks




TE Part # 1924487-2 MOUNTING CLIP, AMPSEAL 16



TE Part # CAT-D485-B128 Backshells, DEUTSCH DTM



TE Part # DT-RT1 EXT TOOL, FRONT RELEASE



TE Part # 1060-20-0622 PIN, SF, SIZE 20, 14-16, NI/NI



TE Part # 1060-20-0144 PIN, SF, SIZE 20, 16-22, AU/SN



TE Part # 1060-20-0222 PIN, SF, SIZE 20, 16-22, NI/NI



TE Part # 1060-20-0122 PIN, SF, SIZE 20, 16-22, NI/NI



TE Part # 1060-20-0244 PIN, SF, SIZE 20, 16-22, AU/SN



TE Part # 1060-20-0177 PIN, SF, SIZE 20, 16-22, SN/SN





BOOT, 8P, REC, ST, BLK


TE Part # CAT-D48-SFT273 DEUTSCH Stamped and Formed Contacts

Also in the Series | DEUTSCH DT





Automotive Connector Caps & Covers (19)



Automotive Connector Locks & Position Assurance(74)



Automotive Housings(620)



Connector Backshells(58)



Connector Seals & Cavity Plugs(6)




Connector Strain Relief(28)



Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(27)




PCB Headers & Receptacles(103)

# Also in the Series | DEUTSCH DTM



Automotive Connector Caps & Covers (7)



Automotive Connector Locks & Position Assurance(17)



Automotive Housings(100)





Connector Strain Relief(28)



Insertion & Extraction Tools(2)



PCB Headers & Receptacles(36)



## Customers Also Bought



REC, 20P, BLK, E, RNG, 16/20, P















TE Part #2392901-1 EVC500, RELAY, SPSTN

## **Documents**

**Product Drawings** 

REC, 8P, BLK, N, B

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_DTM04-08PB\_99\_c-dtm04-08pb-99.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DTM04-08PB\_99\_c-dtm04-08pb-99.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DTM04-08PB\_99\_c-dtm04-08pb-99.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Housing for Male Terminals, Wire-to-Wire, 8 Position, .165 in [4.19 mm] Centerline, Sealable, Black, Wire & Cable, Power & Signal, Hybrid



## Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

**CONNECTOR SELECTOR** 

English

**Product Specifications** 

**Application Specification** 

English

Agency Approvals

**UL Report** 

English