

#### KISSLING | KISSLING Series 29

TE Internal #: K1060283 Power Relays, Standard, Monostable, DC, 10 mW Coil Power Rating DC, 76 Ω Coil Resistance, Coil Suppression Diode, KISSLING Series 29

#### View on TE.com >

Relays, Contactors & Switches > Relays > Power Relays > Power Relay, 75A, Standard, Monostable, DC



Power Relay Type: Standard

Coil Magnetic System: Monostable, DC

Coil Power Rating DC: 10 mW

Coil Resistance: 76  $\Omega$ 

Coil Special Features: Coil Suppression Diode

All Power Relay, 75A, Standard, Monostable, DC (19)

## Features

### Product Type Features

Power Relay Type

# connectivity

Standard

## **Electrical Characteristics**

Coil Magnetic System	Monostable, DC	
Coil Power Rating DC	10 mW	
Coil Resistance	76 Ω	
Coil Special Features	Coil Suppression Diode	
Coil Voltage Rating	18 VDC, 32 VDC	
Contact Voltage Rating	28 VDC	
Contact Features		
Contact Arrangement	1 Form X (SPST-NO-DM)	
Contact Current Class	75 A	
Contact Current Rating (Max)	75 A	
Contact Material	AgSnO2	
Contact Number of Poles	1	
Relay Terminal Type	Screw Terminals	
	Screw reminals	

## 29-013-12

Power Relays, Standard, Monostable, DC, 10 mW Coil Power Rating DC, 76  $\Omega$  Coil Resistance, Coil Suppression Diode, KISSLING Series 29



Relay Mounting Type

Socket

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions	
EU ELV Directive 2000/53/EC	Compliant with Exemptions	
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Pb (92.5% in Component part) Aticle Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.	
Halogen Content	Not Yet Reviewed for halogen content	
Solder Process Capability	Not reviewed for solder process capability	

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



# Also in the Series | KISSLING Series 29

**C** For support call+1 800 522 6752

## 29-013-12

Power Relays, Standard, Monostable, DC, 10 mW Coil Power Rating DC, 76  $\Omega$  Coil Resistance, Coil Suppression Diode, KISSLING Series 29





# Customers Also Bought



HEADER ASSY, Ag SHIELD, KEY B, HVA280-2P	Relay 26-08-08	Relay 26-57-01	Relay 26-60-05

TE Part #K1008006 Relay 26-71-01

## Documents

Product Drawings Relay 29-013-12

German

#### **CAD** Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_29-013-12\_A.2d\_dxf.zip

## 29-013-12

Power Relays, Standard, Monostable, DC, 10 mW Coil Power Rating DC, 76  $\Omega$  Coil Resistance, Coil Suppression Diode, KISSLING Series 29



English

Customer View Model ENG\_CVM\_CVM\_29-013-12\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_29-013-12\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages KISSLING SINGLE POLE POWER RELAYS Series 29 / 75A

English