

KISSLING | KISSLING Series 29

TE Internal #: K1126415

Power Relays, Standard, Monostable, DC, 75 Ω Coil Resistance, Coil Suppression Diode, 32 VDC / 18 VDC Coil Voltage, KISSLING

Series 29

View on TE.com >



Relays, Contactors & Switches > Relays > Power Relays > Power Relay, 120A, Standard, Monostable, DC



Power Relay Type: Standard

Coil Magnetic System: Monostable, DC

Coil Resistance: 75Ω

Coil Special Features: Coil Suppression Diode

Coil Voltage Rating: 18 VDC, 32 VDC

All Power Relay, 120A, Standard, Monostable, DC (14)

Features

Product Type Features

Power Relay Type

Electrical Characteristics	
Coil Magnetic System	Monostable, DC
Coil Resistance	75 Ω
Coil Special Features	Coil Suppression Diode
Coil Voltage Rating	18 VDC, 32 VDC
Contact Voltage Rating	28 VDC

Standard

Contact Features

Contact Arrangement	1 Form X (SPST-NO-DM)
Contact Current Class	120 A
Contact Current Rating (Max)	120 A
Contact Material	AgSnO2
Contact Number of Poles	1
Relay Terminal Type	Screw Terminals

Mechanical Attachment

Relay Mounting Type	Bracket	



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Pb (92.5% in Component part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | KISSLING Series 29





Customers Also Bought



TE Part #DT04-6P-EP14

REC, 6P, BLK, BUSBAR 2X3, NICKEL



TE Part #K1126416 Relay 29-011-12A



TE Part #K1060611 Power Relay, 300A, Standard, Monostable, DC



TE Part #K1131955 Relay 29-511-12A







TE Part #K1162562 Relay 29-111-12-A-961

Documents

Product Drawings

Relay 29-111-12A

German

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_29-111-12A_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_29-111-12A_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_29-111-12A_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Power Relays, Standard, Monostable, DC, 75 Ω Coil Resistance, Coil Suppression Diode, 32 VDC / 18 VDC Coil Voltage, KISSLING Series 29



Datasheets & Catalog Pages

KISSLING SINGLE POLE POWER RELAYS Series 29 / 120A

English