35-314-131-S-902 V ACTIVE



KISSLING | KISSLING Series 35

TE Internal #: K1145222

300 A Battery Disconnect Switch, 32 VDC, 1 Pole, M10, 0 Auxillary

Positions, Angle, T-Handle, Not Removable, Black Handle,

KISSLING Series 35

View on TE.com >



Relays, Contactors & Switches > Switches > Battery Disconnect Switches > Battery Disconnector, 300A, 1 Pole



Operating Voltage: 32 VDC

Switch Main Contact Current Rating: 300 A

Number of Poles: 1

Termination Thread Size: M10 Number of Auxiliary Contacts: 0

All Battery Disconnector, 300A, 1 Pole (4)

Features

Product Type Features

Sealed Rotary Switch	Yes
Configuration Features	
Number of Poles	1
Number of Auxiliary Contacts	0
Switch Keying Option	Not Removable
Electrical Characteristics	
Operating Voltage	32 VDC
Switch Main Contact Current Rating	300 A
Body Features	
Operating Handle Color	Black
Mechanical Attachment	
Termination Thread Size	M10

Angle

T-Handle

Dimensions

Switch Mounting Option

Operating Handle Type



Centerline Between Flange Screw Holes	62 mm[2.44 in]
Screw Hole Diameter	7.2 mm[.283 in]
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Pb (3.1% in Component part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-AL4-SBD353001
Battery Disconnector, 300A, 1 Pole



TE Part # CAT-AL4-SBD354001 Battery Disconnector, 400A, 1 Pole






Also in the Series | KISSLING Series 35



Battery Disconnect Switches(166)




Customers Also Bought



TE Part #211400-1 Cable/Panel Mount Connector, CPC Series 1



Battery Disconnector 35-314-131-S-901



TE Part #66105-2 III+ SKT,24-20,TIN-LEAD,LP



Battery Disconnector 35-514-231-R-901

Documents

Product Drawings

Battery Disconnector 35-314-131-S-902

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_35-314-131-S-902_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_35-314-131-S-902_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_35-314-131-S-902_A.3d_stp.zip

300 A Battery Disconnect Switch, 32 VDC, 1 Pole, M10, 0 Auxillary Positions, Angle, T-Handle, Not Removable, Black Handle, KISSLING Series 35



English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

KISSLING BATTERY DISCONNECTOR Series 35 / 400A

English