ANT-LTE-VDP-2000-SMA V ACTIVE

TE Internal #: L9000176-01

Module Antenna, Wide Band, Cellular / LTE, Remote Mount, Adhesive, SMA, Omnidirectional, Single Port, Gain 3 < 6 dBi

View on TE.com >



Antennas



Wireless Application: Cat-M/NB-IoT, Cellular, LTE

Mounting Location: Remote
Mounting Type: Adhesive
Antenna Termination: SMA
Antenna Type: Module

Features

Product Type Features

Antenna Termination	SMA
Configuration Features	
Antenna Style	Whip
Mounting Location	Remote
Antenna Type	Module
Band Type	Wide Band
Port Configuration	Single Port
Electrical Characteristics	
VSWR (Max)	<1.7:1
Impedance	50 Ω
Signal Characteristics	
Gain (Max)	4.5 dB
Frequency Band	698 – 960 MHz

Body Features

Peak Gain

Product Weight	49 g[1.72839 oz]
Troduct Weight	47 9[1.72037 02]

617 – 6000

3 < 6 dBi

Mechanical Attachment

Nominal Frequency Range



Polarization	Linear
Mounting Type	Adhesive
Dimensions	
Cable Length	2 m[6.56 ft]
Product Width	22 mm[.87 in]
Product Length	115 mm[4.53 in]
Product Height	6.3 mm[.25 in]
Operation/Application	
Directionality	Omnidirectional
Industry Standards	
Wireless Application	Cat-M/NB-IoT, Cellular, LTE
Primary Application	Cellular, LTE

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) SVHC > Threshold: Pb (4% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished



product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts









Customers Also Bought



















Documents

Datasheets & Catalog Pages
Remote Adhesive-Mount Cellular Antenna

ANT-LTE-VDP-2000-SMA

Module Antenna, Wide Band, Cellular / LTE, Remote Mount, Adhesive, SMA, Omnidirectional, Single Port, Gain 3 < 6 dBi



English