

RAYCHEM | RAYCHEM ATUM

TE Internal #: NB10892001 Black, 3:1, Dual Wall Tubing, Shrinks To .059 in [1.5 mm], Irradiated Modified Polyolefin, .177 in [4.5 mm] Inner Diameter, RAYCHEM ATUM

View on TE.com >

Heat Shrink Tubing > ATUM 4:1 dual wall heat shrink tubing



Primary Product Color: Black

Wall Type: Dual Wall

Expanded Inside Diameter (Min): 4.5 mm [.177 in]

Recovered Inside Diameter (Max): 1.5 mm [.059 in]

Shrink Ratio: 3:1

All ATUM 4:1 dual wall heat shrink tubing (135)



Features

Product Type Features

Wall Type	Dual Wall
Electrical Characteristics	
Operating Voltage (Max)	.6 kV
Body Features	
Fluid Type	Aviation Fuel, Chemicals/Solvents, De-Icing Fluid, Diesel Fuel, Hydraulic Fluid, Lubricating Oil
Primary Product Color	Black
Shrink Ratio	3:1
Primary Product Material	Irradiated Modified Polyolefin
Flexibility	Semi-Flexible
Dimensions	
Recovered Wall Thickness (Tolerance)	.3 mm[.012 in]

NB10892001

Black, 3:1, Dual Wall Tubing, Shrinks To .059 in [1.5 mm], Irradiated Modified Polyolefin, .177 in [4.5 mm] Inner Diameter, RAYCHEM ATUM



Recovered Wall Thickness (Nominal)	1 mm[.039 in]		
Product Length	1220 mm[48.031 in]		
Expanded Inside Diameter (Min)	4.5 mm[.177 in]		
Recovered Inside Diameter (Max)	1.5 mm[.059 in]		
Tubing Size Range	1.5 – 4.5 mm[.059 – .177 in]		
Usage Conditions			
Shrink Temperature (Min)	80 °C		
Tubing Flammability Type	Flame-Retardant		
Operating Temperature Range	-55 – 110 °C		
Recovery Temperature	110 °C		
Operation/Application			
Mechanical Resistance	Fluids, Mechanical Damage, Strain Relief		
Product Availability			
Applicable Region	Global		
Packaging Features			
Packaging Method	Bag & Box		

Other

Meets	Low	Outgas	ssing	Req	uirements
		9.00			

Product Source

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU

EU ELV Directive 2000/53/EC

China RoHS 2 Directive MIIT Order No 32, 2016

EU REACH Regulation (EC) No. 1907/2006

Halogen Content

Compliant

Czech Republic

No

Compliant

No Restricted Materials Above Threshold

Current ECHA Candidate List: JUNE 2023 (235)

Candidate List Declared Against: JUNE

2023 (235)

SVHC > Threshold:

DBMC (1.54% in Component Part)

Article Safe Usage Statements:

Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Not Low Halogen - contains Br or Cl > 900 ppm.

& For support call+1 800 522 6752

NB10892001

Black, 3:1, Dual Wall Tubing, Shrinks To .059 in [1.5 mm], Irradiated Modified Polyolefin, .177 in [4.5 mm] Inner Diameter, RAYCHEM ATUM



Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



TE Part # EG1114-000 CV1981-ST-230V1600W-EU

Also in the Series **RAYCHEM ATUM**



Customers Also Bought



NB10892001

Black, 3:1, Dual Wall Tubing, Shrinks To .059 in [1.5 mm], Irradiated Modified Polyolefin, .177 in [4.5 mm] Inner Diameter, RAYCHEM ATUM





Documents

Product Drawings ATUM-4.5/1.5-0-STK

English

Datasheets & Catalog Pages

ATUM Pages from 9-1773447-9

English

Product Specifications

Application Specification

English