# T4140012021-000 - ACTIVE

#### M12 Connector

TE Internal #: T4140012021-000 Standard Circular Connectors, Wire-to-Panel, 2 Position, Sealable, Printed Circuit Board, Signal, Reverse Gender, Nickel, Brass, M12 Connector

#### View on TE.com >

Connectors > Circular Connectors > Standard Circular Connectors > M12 Panel Mount PCB



Connector System: Wire-to-Panel Number of Positions: 2 Sealable: Yes Connector & Contact Terminates To: Printed Circuit Board Contact Current Rating (Max): 4 A

## All M12 Panel Mount PCB (111)



## Features

| Product Type                          | Connector Assembly    |
|---------------------------------------|-----------------------|
| Accessory Color                       | Black                 |
| Assembly Type                         | Electrical Connector  |
| Connector System                      | Wire-to-Panel         |
| Sealable                              | Yes                   |
| Connector & Contact Terminates To     | Printed Circuit Board |
| Circular Connector Type               | Plug                  |
| Shell Type                            | Metal                 |
| Configuration Features                |                       |
| Keying & Polarized Position Locations | A                     |
| Factory Installed Backshell           | No                    |
| Keying                                | A                     |
| Number of Positions                   | 2                     |

**C** For support call+1 800 522 6752

Standard Circular Connectors, Wire-to-Panel, 2 Position, Sealable, Printed Circuit Board, Signal, Reverse Gender, Nickel, Brass, M12 Connector



| Number of Power Positions  | 0                          |
|--|----------------------------|
| Number of Signal Positions   | 2                          |
| Contacts Preloaded   | Yes                        |
| Electrical Characteristics   |                            |
| Operating Voltage  | 250 VAC                    |
| Body Features  |                            |
| Peripheral Seal Material   | Silicone                   |
| Environmental Protection   | IP67                       |
| O-Ring Material  | Silicone                   |
| Environmental Protection Type                                      | Elastomer Sealed           |
| Shell Plating Material   | Nickel                     |
|  | NICKEI                     |
| Shell Base Material  | Brass                      |
| Shell Base Material<br>Circular Connector Insulation Material Type |                            |
|  | Brass                      |
| Circular Connector Insulation Material Type                        | Brass                      |
| Circular Connector Insulation Material Type Contact Features       | Brass<br>Polyamide 66 GF25 |

## Mechanical Attachment

| Polarization Code             | A                         |
|-------------------------------|---------------------------|
| Housing Features              |                           |
| Circular Connector Shell Size | 18                        |
| Usage Conditions              |                           |
| IP Water Sealing Level        | IP67                      |
| Operating Temperature Range   | -40 – 85 °C[-40 – 185 °F] |
| Operation/Application         |                           |
| Circuit Application           | Signal                    |
| Shielded                      | No                        |
| Industry Standards            |                           |
| UL Flammability Rating        | UL 94HB                   |
| Packaging Features            |                           |
| Packaging Quantity            | 1                         |

Standard Circular Connectors, Wire-to-Panel, 2 Position, Sealable, Printed Circuit Board, Signal, Reverse Gender, Nickel, Brass, M12 Connector



#### Other

| Field Serviceable   | No   |
|---|--|
| Product Compliance<br>For compliance documentation, visit the product page on TE.com> |  |
| EU RoHS Directive 2011/65/EU  | Compliant with Exemptions  |
| EU ELV Directive 2000/53/EC   | Compliant with Exemptions  |
| China RoHS 2 Directive MIIT Order No 32, 2016   | Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006  | Current ECHA Candidate List: JUNE 2023<br>(235)<br>Candidate List Declared Against: JUNE<br>2023 (235)<br>SVHC > Threshold:<br>Pb (4% in Component Part)<br>Aticle Safe Usage Statements:<br>Do not eat, drink or smoke when using this product. Wash thoroughly after<br>handling. Recycle if possible and dispose of the article by following all applicable<br>governmental regulations relevant to your geographic location. |
| Halogen Content   | Low Halogen - Br, Cl, F, I < 900 ppm per<br>homogenous material. Also BFR/CFR/PVC<br>Free  |
| Solder Process Capability   | Not applicable for solder process capability   |

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**




Standard Circular Connectors, Wire-to-Panel, 2 Position, Sealable, Printed Circuit Board, Signal, Reverse Gender, Nickel, Brass, M12 Connector





## Customers Also Bought









## Documents

**Product Drawings** M12,REAR MOUNTING,MALE,A CODE,2P

English

**CAD** Files

3D PDF

3D

**Customer View Model** ENG\_CVM\_CVM\_T4140012021-000\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_T4140012021-000\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_T4140012021-000\_B.3d\_stp.zip

Standard Circular Connectors, Wire-to-Panel, 2 Position, Sealable, Printed Circuit Board, Signal, Reverse Gender, Nickel, Brass, M12 Connector



## English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

### M8 / M12 Connector System Catalog

English

M8 / M12 Connector System Catalog

Japanese

Product Specifications

English

Agency Approvals

UL

English